

WASHINGTON ankle safety shoes DIELECTRIC

» Shoes » Safety shoes » Ankle

Technical sheet

WASHINGTON ankle safety shoes DIELECTRIC

Product code: 6400-SBP



upper	cowhide leather coated, brushed in a thickness of 1,8 - 2,0 mm
lining	laminated breathable fabric MESH
inner insole	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH
outsole	PU/RUBBER - up to 300°C, resistant to fuel oils
size	40 - 47
standard	EN ISO 20345:2011
version	SBEP HRO SRC - with composite toe cap and kevlar midsole - the lower part of the footwear is resistant to elektrik shock at a voltage up to 10kV according to EN 50321

Properties

PL Midsole penetration protection nonmetallic - PL	No
PS Midsole penetration protection nonmetallic - PS	No
SR Antislip prop. on ceramic with glycerol	No
WPA Water resistant upper	No
HRO Resist. of the outsole against contact heat	Yes

WASHINGTON ankle safety shoes DIELECTRIC

» Shoes » Safety shoes » Ankle

WR Water resistant	No
WRU Water resistant upper	No
CI Insulation against cold	No
HI Insulation of the outsole against heat	No
FO Resist. of the outsole against fuel oils	Yes
P Midsole penetration protection	Yes
E Energy absorption in the heel area	Yes
M Instep protection	No
A Antistatic properties	No
AN Ankle protection	No
CR Cut resistant upper	No
SRA Antislip prop. on ceramic tile with SLS	Yes
SRB Antislip prop. on smooth steel with glycerol	Yes
SRC Antislip resistance SRA + SRB	Yes
Free-tex Membrane	No
Michelin Michelin® sole	No
BOA BOA Fit System	No
NON-METALIC Footwear without metal parts	No
ESD antistatic properties ESD	No
Winter Winter footwear	No
ANTICUT Anti-cut boots	No
Standard	20345:2012
Shoe marking	SB

Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
40	1,59 kg	1,88 kg	260 mm	320 mm	115 mm	545 mm	615 mm	340 mm	20,00 kg	266,7 mm
41	1,60 kg	1,92 kg	260 mm	320 mm	115 mm	545 mm	615 mm	340 mm	20,40 kg	273,3 mm
42	1,64 kg	1,93 kg	260 mm	320 mm	115 mm	545 mm	615 mm	340 mm	21,00 kg	280,0 mm
43	1,71 kg	2,06 kg	275 mm	350 mm	130 mm	580 mm	670 mm	390 mm	21,80 kg	286,7 mm
44	1,74 kg	2,10 kg	275 mm	350 mm	130 mm	580 mm	670 mm	390 mm	22,40 kg	293,3 mm
45	1,90 kg	2,25 kg	275 mm	350 mm	130 mm	580 mm	670 mm	390 mm	23,60 kg	300,0 mm
46	1,94 kg	2,27 kg	275 mm	350 mm	130 mm	580 mm	670 mm	390 mm	23,80 kg	306,7 mm
47	1,98 kg	2,35 kg	275 mm	350 mm	130 mm	580 mm	670 mm	390 mm	24,80 kg	313,4 mm

Business parameters

Tarric	64034000
Country	CN
Weight	1,50 kg
Add Unit	NPR
Add Quantity	1