

SYDNEY low cut outdoor shoes

» Shoes » Outdoor shoes » Low cut

Technical sheet

SYDNEY low cut outdoor shoes

Product code: 4225-60



upper	breathable, abrasion resistant textile DUO with TPU print
lining	laminated breathable fabric MESH
inner insole	HI-POLY – anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
outsole	EVA/RUBBER – glued construction
size	39 – 47
usability	shoes suitable for daily wear and outdoor activities
version	black colour

Properties

PL Midsole penetration protection nonmetallic - PL	No
PS Midsole penetration protection nonmetallic - PS	No
SR Antislip prop. on ceramic with glycerol	No
WPA Water resistant upper	No
HRO Resist. of the outsole against contact heat	No
WR Water resistant	No
WRU Water resistant upper	No

SYDNEY low cut outdoor shoes

» Shoes » Outdoor shoes » Low cut

CI Insulation against cold	No
HI Insulation of the outsole against heat	No
FO Resist. of the outsole against fuel oils	No
P Midsole penetration protection	No
E Energy absorption in the heel area	No
M Instep protection	No
A Antistatic properties	No
AN Ankle protection	No
CR Cut resistant upper	No
SRA Antislip prop. on ceramic tile with SLS	No
SRB Antislip prop. on smooth steel with glycerol	No
SRC Antislip resistance SRA + SRB	No
Free-tex Membrane	No
Michelin Michelin® sole	No
BOA BOA Fit System	No
NON-METALIC Footwear without metal parts	No
ESD antistatic properties ESD	No
Winter Winter footwear	No
ANTICUT Anti-cut boots	No

Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
39	0,68 kg	0,95 kg	230 mm	335 mm	120 mm	490 mm	620 mm	355 mm	10,60 kg	0,0 mm
40	0,69 kg	0,98 kg	230 mm	335 mm	120 mm	490 mm	620 mm	355 mm	10,80 kg	0,0 mm
41	0,71 kg	0,99 kg	230 mm	335 mm	120 mm	490 mm	620 mm	355 mm	11,00 kg	0,0 mm
42	0,76 kg	1,05 kg	230 mm	335 mm	120 mm	490 mm	620 mm	355 mm	11,40 kg	0,0 mm
43	0,77 kg	1,08 kg	240 mm	350 mm	125 mm	490 mm	640 mm	375 mm	12,00 kg	0,0 mm
44	0,87 kg	1,17 kg	240 mm	350 mm	125 mm	490 mm	640 mm	375 mm	12,70 kg	0,0 mm
45	0,88 kg	1,18 kg	240 mm	350 mm	125 mm	490 mm	640 mm	375 mm	12,90 kg	0,0 mm
46	0,91 kg	1,21 kg	240 mm	350 mm	125 mm	490 mm	640 mm	375 mm	13,20 kg	0,0 mm
47	0,96 kg	1,29 kg	240 mm	350 mm	125 mm	490 mm	640 mm	375 mm	13,40 kg	0,0 mm

Business parameters

Tarric	64041990
Country	CN
Weight	1,20 kg
Add Unit	NPR
Add Quantity	1