

SANDIEGO safety boots

» Shoes » Safety shoes » Gumboots

Technical sheet SANDIEGO safety boots



Product code: 1010-S5



upper	PVC/NITRIL – acid-resistant
outsole	PVC/NITRIL – acid-resistant
**inner insole **	HI-POLY – anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic#Tab
size	40 – 47
standard	EN ISO 20345:2011
version	S5 SRA – with steel toe cap and midsole

Properties

PL Midsole penetration protection nonmetallic - PL	No
PS Midsole penetration protection nonmetallic - PS	No
SR Antislip prop. on ceramic with glycerol	No
WPA Water resistant upper	No
HRO Resist. of the outsole against contact heat	No
WR Water resistant	No
WRU Water resistant upper	No
CI Insulation against cold	No

SANDIEGO safety boots

» Shoes » Safety shoes » Gumboots

HI Insulation of the outsole against heat	No
FO Resist. of the outsole against fuel oils	Yes
P Midsole penetration protection	No
E Energy absorption in the heel area	Yes
M Instep protection	No
A Antistatic properties	Yes
AN Ankle protection	No
CR Cut resistant upper	No
SRA Antislip prop. on ceramic tile with SLS	Yes
SRB Antislip prop. on smooth steel with glycerol	No
SRC Antislip resistance SRA + SRB	No
Free-tex Membrane	No
Michelin Michelin® sole	No
BOA BOA Fit System	No
NON-METALIC Footwear without metal parts	No
ESD antistatic properties ESD	No
Winter Winter footwear	No
ANTICUT Anti-cut boots	No
Standard	20345:2012
Shoe marking	S5

Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
40	2,59 kg	3,06 kg	340 mm	420 mm	130 mm	450 mm	700 mm	440 mm	19,99 kg	0,0 mm
41	2,70 kg	3,16 kg	340 mm	420 mm	130 mm	450 mm	700 mm	440 mm	20,96 kg	0,0 mm
42	2,75 kg	3,22 kg	340 mm	420 mm	130 mm	450 mm	700 mm	440 mm	20,63 kg	0,0 mm
43	2,91 kg	3,38 kg	340 mm	420 mm	130 mm	450 mm	700 mm	440 mm	22,00 kg	0,0 mm
44	3,04 kg	3,51 kg	340 mm	420 mm	130 mm	450 mm	700 mm	440 mm	22,73 kg	0,0 mm
45	3,30 kg	3,76 kg	340 mm	420 mm	130 mm	450 mm	700 mm	440 mm	24,23 kg	0,0 mm
46	3,39 kg	3,86 kg	340 mm	420 mm	130 mm	450 mm	700 mm	440 mm	24,82 kg	0,0 mm
47	3,52 kg	4,00 kg	340 mm	420 mm	130 mm	450 mm	700 mm	440 mm	25,65 kg	0,0 mm

Business parameters

Tarric	64011000
Country	CN
Weight	2,90 kg
Add Unit	NPR
Add Quantity	1