

# SANTIAGO ankle occupational shoes

» Shoes » Occupational shoes » Ankle

## Technical sheet

### SANTIAGO ankle occupational shoes

Product code: 4170-OB



|                     |                                                                                                 |
|---------------------|-------------------------------------------------------------------------------------------------|
| <b>upper</b>        | cowhide leather NUBUCK in a thickness of 1,9 - 2,1 mm                                           |
| <b>lining</b>       | breathable thermo-insulation MEMBRANE FREE-TEX®                                                 |
| <b>inner insole</b> | HI-POLY - anatomically shaped lightweight polyurethane foam coated with fabric MESH, antistatic |
| <b>outsole</b>      | EVA/RUBBER - resistant to fuel oils, antistatic, antislip, glued construction                   |
| <b>size</b>         | 36 - 48                                                                                         |
| <b>standard</b>     | EN ISO 20347:2012                                                                               |
| <b>version</b>      | OB E WRU SRA - without steel toe cap, hydrophobic, FREE-TEX®                                    |

## Properties

|                                                           |     |
|-----------------------------------------------------------|-----|
| <b>PL</b> Midsole penetration protection nonmetallic - PL | No  |
| <b>PS</b> Midsole penetration protection nonmetallic - PS | No  |
| <b>SR</b> Antislip prop. on ceramic with glycerol         | No  |
| <b>WPA</b> Water resistant upper                          | No  |
| <b>HRO</b> Resist. of the outsole against contact heat    | No  |
| <b>WR</b> Water resistant                                 | No  |
| <b>WRU</b> Water resistant upper                          | Yes |

# SANTIAGO ankle occupational shoes

» Shoes » Occupational shoes » Ankle

|              |                                              |            |
|--------------|----------------------------------------------|------------|
| CI           | Insulation against cold                      | No         |
| HI           | Insulation of the outsole against heat       | No         |
| FO           | Resist. of the outsole against fuel oils     | Yes        |
| P            | Midsole penetration protection               | No         |
| E            | Energy absorption in the heel area           | Yes        |
| M            | Instep protection                            | No         |
| A            | Antistatic properties                        | No         |
| AN           | Ankle protection                             | No         |
| CR           | Cut resistant upper                          | No         |
| SRA          | Antislip prop. on ceramic tile with SLS      | Yes        |
| SRB          | Antislip prop. on smooth steel with glycerol | No         |
| SRC          | Antislip resistance SRA + SRB                | No         |
| Free-tex     | Membrane                                     | Yes        |
| Michelin     | Michelin® sole                               | No         |
| BOA          | BOA Fit System                               | No         |
| NON-METALIC  | Footwear without metal parts                 | No         |
| ESD          | antistatic properties ESD                    | No         |
| Winter       | Winter footwear                              | No         |
| ANTICUT      | Anti-cut boots                               | No         |
| Standard     |                                              | 20347:2012 |
| Shoe marking |                                              | OB         |

## Logistics parameters

| Velikost | Net weight | Gross weight | Sales box - width | Sales box - length | Sales box - height | Group packaging - width | Group packaging - length | Group packaging - height | Group packaging - weight | Vnitřní délka obuvi |
|----------|------------|--------------|-------------------|--------------------|--------------------|-------------------------|--------------------------|--------------------------|--------------------------|---------------------|
| 36       | 1,03 kg    | 1,30 kg      | 270 mm            | 315 mm             | 110 mm             | 570 mm                  | 580 mm                   | 335 mm                   | 14,30 kg                 | 240,1 mm            |
| 37       | 1,06 kg    | 1,35 kg      | 270 mm            | 315 mm             | 110 mm             | 570 mm                  | 580 mm                   | 335 mm                   | 14,60 kg                 | 246,8 mm            |
| 38       | 1,12 kg    | 1,41 kg      | 270 mm            | 315 mm             | 110 mm             | 570 mm                  | 580 mm                   | 335 mm                   | 15,20 kg                 | 253,5 mm            |
| 39       | 1,14 kg    | 1,44 kg      | 270 mm            | 315 mm             | 110 mm             | 570 mm                  | 580 mm                   | 335 mm                   | 15,80 kg                 | 260,1 mm            |
| 40       | 1,19 kg    | 1,49 kg      | 270 mm            | 315 mm             | 110 mm             | 570 mm                  | 580 mm                   | 335 mm                   | 16,00 kg                 | 266,8 mm            |
| 41       | 1,21 kg    | 1,21 kg      | 270 mm            | 315 mm             | 110 mm             | 570 mm                  | 580 mm                   | 335 mm                   | 16,20 kg                 | 273,5 mm            |
| 42       | 1,26 kg    | 1,60 kg      | 290 mm            | 345 mm             | 125 mm             | 610 mm                  | 630 mm                   | 365 mm                   | 17,60 kg                 | 280,1 mm            |
| 43       | 1,30 kg    | 1,66 kg      | 290 mm            | 345 mm             | 125 mm             | 610 mm                  | 630 mm                   | 365 mm                   | 18,40 kg                 | 286,8 mm            |
| 44       | 1,39 kg    | 1,73 kg      | 290 mm            | 345 mm             | 125 mm             | 610 mm                  | 630 mm                   | 365 mm                   | 19,00 kg                 | 293,5 mm            |
| 45       | 1,46 kg    | 1,81 kg      | 290 mm            | 345 mm             | 125 mm             | 610 mm                  | 630 mm                   | 365 mm                   | 19,60 kg                 | 300,1 mm            |
| 46       | 1,53 kg    | 1,92 kg      | 305 mm            | 370 mm             | 130 mm             | 650 mm                  | 650 mm                   | 390 mm                   | 20,80 kg                 | 306,8 mm            |
| 47       | 1,55 kg    | 1,93 kg      | 305 mm            | 370 mm             | 130 mm             | 650 mm                  | 650 mm                   | 390 mm                   | 21,00 kg                 | 313,5 mm            |
| 48       | 1,56 kg    | 1,95 kg      | 305 mm            | 370 mm             | 130 mm             | 650 mm                  | 650 mm                   | 390 mm                   | 21,20 kg                 | 320,2 mm            |

## Business parameters

|          |          |
|----------|----------|
| Tarric   | 64039113 |
| Country  | CN       |
| Weight   | 1,70 kg  |
| Add Unit | NPR      |

# SANTIAGO ankle occupational shoes

» Shoes » Occupational shoes » Ankle

**Add Quantity**    1