

SPLIT safety sandal

» Shoes » Safety shoes » Sandals

Technical sheet

SPLIT safety sandal

Product code: 3345-S1



upper	brushed cow suede leather VELOUR in a thickness of 1,6 - 1,8 mm
lining	MESH fabric with absorbency
inner insole	lightweight polyurethan foam, coated with textile MESH, antistatic
outsole	PU/PU – resistant to fuel oils, antistatic, antislip, double density injection
size	36 – 50
standard	EN ISO 20345:2011
version	S1 SRC – with steel toe cap

Properties

PL Midsole penetration protection nonmetallic - PL	No
PS Midsole penetration protection nonmetallic - PS	No
SR Antislip prop. on ceramic with glycerol	No
WPA Water resistant upper	No
HRO Resist. of the outsole against contact heat	No
WR Water resistant	No
WRU Water resistant upper	No

SPLIT safety sandal

» Shoes » Safety shoes » Sandals

CI Insulation against cold	No
HI Insulation of the outsole against heat	No
FO Resist. of the outsole against fuel oils	Yes
P Midsole penetration protection	No
E Energy absorption in the heel area	Yes
M Instep protection	No
A Antistatic properties	Yes
AN Ankle protection	No
CR Cut resistant upper	No
SRA Antislip prop. on ceramic tile with SLS	Yes
SRB Antislip prop. on smooth steel with glycerol	Yes
SRC Antislip resistance SRA + SRB	Yes
Free-tex Membrane	No
Michelin Michelin® sole	No
BOA BOA Fit System	No
NON-METALIC Footwear without metal parts	No
ESD antistatic properties ESD	No
Winter Winter footwear	No
ANTICUT Anti-cut boots	No
Standard	20345:2012
Shoe marking	S1

Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
36	1,07 kg	1,23 kg	205 mm	310 mm	115 mm	430 mm	600 mm	340 mm	13,00 kg	232,3 mm
37	1,09 kg	1,27 kg	205 mm	310 mm	115 mm	430 mm	600 mm	340 mm	13,40 kg	239,0 mm
38	1,14 kg	1,31 kg	205 mm	310 mm	115 mm	430 mm	600 mm	340 mm	13,80 kg	245,7 mm
39	1,17 kg	1,33 kg	205 mm	310 mm	115 mm	430 mm	600 mm	340 mm	14,40 kg	252,3 mm
40	1,23 kg	1,40 kg	205 mm	310 mm	115 mm	430 mm	600 mm	340 mm	14,60 kg	259,0 mm
41	1,28 kg	1,48 kg	205 mm	310 mm	115 mm	430 mm	600 mm	340 mm	15,40 kg	265,7 mm
42	1,30 kg	1,49 kg	205 mm	310 mm	115 mm	430 mm	600 mm	340 mm	15,80 kg	272,3 mm
43	1,36 kg	1,54 kg	210 mm	330 mm	120 mm	440 mm	630 mm	350 mm	16,00 kg	279,0 mm
44	1,37 kg	1,55 kg	210 mm	330 mm	120 mm	440 mm	630 mm	350 mm	16,60 kg	285,7 mm
45	1,43 kg	1,68 kg	220 mm	355 mm	125 mm	450 mm	645 mm	380 mm	17,60 kg	292,3 mm
46	1,47 kg	1,71 kg	220 mm	355 mm	125 mm	450 mm	645 mm	380 mm	16,80 kg	299,0 mm
47	1,54 kg	1,74 kg	220 mm	355 mm	125 mm	450 mm	645 mm	380 mm	18,00 kg	305,7 mm
48	1,73 kg	1,92 kg	220 mm	355 mm	125 mm	450 mm	645 mm	380 mm	19,10 kg	312,4 mm
49	0,00 kg	0,00 kg	0 mm	0 mm	0 mm	0 mm	0 mm	0 mm	0,00 kg	319,0 mm
50	0,00 kg	0,00 kg	0 mm	0 mm	0 mm	0 mm	0 mm	0 mm	0,00 kg	325,7 mm

Business parameters

Tarric	64034000
Country	CN
Weight	1,50 kg

SPLIT safety sandal

» Shoes » Safety shoes » Sandals

Add Unit NPR
Add Quantity 1