

# SHEFFIELD high heel safety shoes, winter design

» Shoes » Safety shoes » Boots

## Technical sheet

### SHEFFIELD high heel safety shoes, winter design

Product code: 2890-S3W



|                     |                                                                                |
|---------------------|--------------------------------------------------------------------------------|
| <b>upper</b>        | cowhide leather with pattern in a thickness of 1,8 – 2,0 mm                    |
| <b>lining</b>       | hair plush DELTA                                                               |
| <b>inner insole</b> | anatomically shaped, coated with hair plush DELTA, antistatic                  |
| <b>outsole</b>      | PU/PU – resistant to fuel oils, antistatic, antislip, double density injection |
| <b>size</b>         | 36 – 48                                                                        |
| <b>standard</b>     | EN ISO 20347:2012                                                              |
| <b>version</b>      | S3W CI SRC – with steel toe cap, winter design                                 |

## Properties

|                                                           |    |
|-----------------------------------------------------------|----|
| <b>PL</b> Midsole penetration protection nonmetallic - PL | No |
| <b>PS</b> Midsole penetration protection nonmetallic - PS | No |
| <b>SR</b> Antislip prop. on ceramic with glycerol         | No |
| <b>WPA</b> Water resistant upper                          | No |
| <b>HRO</b> Resist. of the outsole against contact heat    | No |
| <b>WR</b> Water resistant                                 | No |

# SHEFFIELD high heel safety shoes, winter design

» Shoes » Safety shoes » Boots

|                                                         |            |
|---------------------------------------------------------|------------|
| <b>WRU</b> Water resistant upper                        | Yes        |
| <b>CI</b> Insulation against cold                       | Yes        |
| <b>HI</b> Insulation of the outsole against heat        | No         |
| <b>FO</b> Resist. of the outsole against fuel oils      | Yes        |
| <b>P</b> Midsole penetration protection                 | Yes        |
| <b>E</b> Energy absorption in the heel area             | Yes        |
| <b>M</b> Instep protection                              | No         |
| <b>A</b> Antistatic properties                          | Yes        |
| <b>AN</b> Ankle protection                              | No         |
| <b>CR</b> Cut resistant upper                           | No         |
| <b>SRA</b> Antislip prop. on ceramic tile with SLS      | Yes        |
| <b>SRB</b> Antislip prop. on smooth steel with glycerol | Yes        |
| <b>SRC</b> Antislip resistance SRA + SRB                | Yes        |
| <b>Free-tex</b> Membrane                                | No         |
| <b>Michelin</b> Michelin® sole                          | No         |
| <b>BOA</b> BOA Fit System                               | No         |
| <b>NON-METALIC</b> Footwear without metal parts         | No         |
| <b>ESD</b> antistatic properties ESD                    | No         |
| <b>Winter</b> Winter footwear                           | Yes        |
| <b>ANTICUT</b> Anti-cut boots                           | No         |
| <b>Standard</b>                                         | 20345:2012 |
| <b>Shoe marking</b>                                     | S3         |

## Logistics parameters

| Velikost | Net weight | Gross weight | Sales box - width | Sales box - length | Sales box - height | Group packaging - width | Group packaging - length | Group packaging - height | Group packaging - weight | Vnitřní délka obuvi |
|----------|------------|--------------|-------------------|--------------------|--------------------|-------------------------|--------------------------|--------------------------|--------------------------|---------------------|
| 36       | 1,29 kg    | 1,60 kg      | 315 mm            | 315 mm             | 115 mm             | 600 mm                  | 645 mm                   | 340 mm                   | 17,40 kg                 | 239,0 mm            |
| 37       | 1,30 kg    | 1,62 kg      | 315 mm            | 315 mm             | 115 mm             | 600 mm                  | 645 mm                   | 340 mm                   | 17,60 kg                 | 245,7 mm            |
| 38       | 1,33 kg    | 1,65 kg      | 315 mm            | 315 mm             | 115 mm             | 600 mm                  | 645 mm                   | 340 mm                   | 17,80 kg                 | 252,3 mm            |
| 39       | 1,35 kg    | 1,64 kg      | 315 mm            | 315 mm             | 115 mm             | 600 mm                  | 645 mm                   | 340 mm                   | 18,10 kg                 | 259,0 mm            |
| 40       | 1,42 kg    | 1,69 kg      | 315 mm            | 315 mm             | 115 mm             | 600 mm                  | 645 mm                   | 340 mm                   | 18,40 kg                 | 265,7 mm            |
| 41       | 1,47 kg    | 1,76 kg      | 315 mm            | 315 mm             | 115 mm             | 600 mm                  | 645 mm                   | 340 mm                   | 18,80 kg                 | 272,3 mm            |
| 42       | 1,48 kg    | 1,77 kg      | 315 mm            | 315 mm             | 115 mm             | 600 mm                  | 645 mm                   | 340 mm                   | 19,00 kg                 | 279,0 mm            |
| 43       | 1,58 kg    | 1,89 kg      | 325 mm            | 325 mm             | 120 mm             | 625 mm                  | 665 mm                   | 345 mm                   | 20,00 kg                 | 285,7 mm            |
| 44       | 1,64 kg    | 1,95 kg      | 325 mm            | 325 mm             | 120 mm             | 625 mm                  | 665 mm                   | 345 mm                   | 20,80 kg                 | 292,3 mm            |
| 45       | 1,69 kg    | 2,02 kg      | 335 mm            | 335 mm             | 125 mm             | 650 mm                  | 695 mm                   | 370 mm                   | 21,60 kg                 | 299,0 mm            |
| 46       | 1,76 kg    | 2,09 kg      | 335 mm            | 335 mm             | 125 mm             | 650 mm                  | 695 mm                   | 370 mm                   | 22,40 kg                 | 305,7 mm            |
| 47       | 1,82 kg    | 2,15 kg      | 335 mm            | 335 mm             | 125 mm             | 650 mm                  | 695 mm                   | 370 mm                   | 22,90 kg                 | 312,4 mm            |
| 48       | 1,89 kg    | 2,22 kg      | 335 mm            | 335 mm             | 125 mm             | 650 mm                  | 695 mm                   | 370 mm                   | 23,60 kg                 | 319,0 mm            |

## Business parameters

|                |          |
|----------------|----------|
| <b>Tarric</b>  | 64034000 |
| <b>Country</b> | CN       |
| <b>Weight</b>  | 1,79 kg  |

# SHEFFIELD high heel safety shoes, winter design

» Shoes » Safety shoes » Boots

**Add Unit**        NPR  
**Add Quantity**    1