

STUTTGART ankle occupational shoes

» Shoes » Occupational shoes » Ankle

Technical sheet

STUTTGART ankle occupational shoes

Product code: 2550-O6ESD



upper	cowhide leather PULL-UP in a thickness of 2,0 - 2,2 mm
lining	breathable thermo-insulation MEMBRANE FREE-TEX®
inner insole	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
outsole	PU/RUBBER - up to 300°C, resistant to fuel oils, antistatic, antislip, double density injection
size	39 - 48
standard	EN ISO 20347:2022, EN ISO 61340-5-1:2016
version	O6 FO HRO SR - without composite toe cap and kevlar midsole, hydrophobic, MEMBRANE FREE-TEX®, ESD

Properties

PL Midsole penetration protection nonmetallic - PL	No
PS Midsole penetration protection nonmetallic - PS	No
SR Antislip prop. on ceramic with glycerol	Yes
WPA Water resistant upper	Yes
HRO Resist. of the outsole against contact heat	Yes

STUTTGART ankle occupational shoes

» Shoes » Occupational shoes » Ankle

WR Water resistant	Yes
WRU Water resistant upper	No
CI Insulation against cold	No
HI Insulation of the outsole against heat	No
FO Resist. of the outsole against fuel oils	Yes
P Midsole penetration protection	No
E Energy absorption in the heel area	Yes
M Instep protection	No
A Antistatic properties	Yes
AN Ankle protection	No
CR Cut resistant upper	No
SRA Antislip prop. on ceramic tile with SLS	No
SRB Antislip prop. on smooth steel with glycerol	No
SRC Antislip resistance SRA + SRB	No
Free-tex Membrane	Yes
Michelin Michelin® sole	No
BOA BOA Fit System	No
NON-METALIC Footwear without metal parts	No
ESD antistatic properties ESD	Yes
Winter Winter footwear	No
ANTICUT Anti-cut boots	No
Standard	20347:2023
Shoe marking	O6

Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
39	1,10 kg	1,35 kg	225 mm	315 mm	120 mm	480 mm	600 mm	340 mm	14,40 kg	260,0 mm
40	1,12 kg	1,38 kg	225 mm	315 mm	120 mm	480 mm	600 mm	340 mm	14,60 kg	266,7 mm
41	1,44 kg	1,73 kg	260 mm	320 mm	115 mm	540 mm	600 mm	335 mm	17,80 kg	273,3 mm
42	1,37 kg	1,67 kg	260 mm	320 mm	115 mm	540 mm	600 mm	335 mm	18,00 kg	280,0 mm
43	1,42 kg	1,81 kg	265 mm	330 mm	125 mm	555 mm	625 mm	360 mm	19,00 kg	286,7 mm
44	1,52 kg	1,87 kg	265 mm	330 mm	125 mm	555 mm	625 mm	360 mm	20,00 kg	293,3 mm
45	1,54 kg	1,90 kg	275 mm	350 mm	125 mm	565 mm	645 mm	365 mm	20,50 kg	300,0 mm
46	1,63 kg	1,95 kg	275 mm	350 mm	125 mm	565 mm	645 mm	365 mm	21,00 kg	306,7 mm
47	1,66 kg	2,02 kg	275 mm	350 mm	125 mm	565 mm	645 mm	365 mm	21,60 kg	313,4 mm
48	1,78 kg	2,08 kg	275 mm	350 mm	125 mm	565 mm	645 mm	365 mm	22,00 kg	320,0 mm

Business parameters

Tarric	64039113
Country	CN
Weight	1,53 kg
Add Unit	NPR
Add Quantity	1