

QUITO ankle occupational shoes

» Shoes » Occupational shoes » Ankle

Technical sheet

QUITO ankle occupational shoes

Product code: 2490-01



upper	cowhide leather in a thickness of 2,0 - 2,2 mm
lining	laminated breathable fabric MESH
inner insole	HI-POLY - anatomically shaped lightweight polyurethane foam coated with fabric MESH, antistatic
outsole	PU/RUBBER - up to 300°C, resistant to fuel oils, antistatic, antislip, double density injection
size	40 - 48
standard	EN ISO 20347:2022
version	01 FO HRO SR - without steel toe cap

Properties

PL Midsole penetration protection nonmetallic - PL	No
PS Midsole penetration protection nonmetallic - PS	No
SR Antislip prop. on ceramic with glycerol	Yes
WPA Water resistant upper	No
HRO Resist. of the outsole against contact heat	Yes
WR Water resistant	No

QUITO ankle occupational shoes

» Shoes » Occupational shoes » Ankle

WRU Water resistant upper	No
CI Insulation against cold	No
HI Insulation of the outsole against heat	No
FO Resist. of the outsole against fuel oils	Yes
P Midsole penetration protection	No
E Energy absorption in the heel area	Yes
M Instep protection	No
A Antistatic properties	Yes
AN Ankle protection	No
CR Cut resistant upper	No
SRA Antislip prop. on ceramic tile with SLS	No
SRB Antislip prop. on smooth steel with glycerol	No
SRC Antislip resistance SRA + SRB	No
Free-tex Membrane	No
Michelin Michelin® sole	No
BOA BOA Fit System	No
NON-METALIC Footwear without metal parts	No
ESD antistatic properties ESD	No
Winter Winter footwear	No
ANTICUT Anti-cut boots	No
Standard	20347:2023
Shoe marking	O1

Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
40	1,08 kg	1,39 kg	260 mm	320 mm	120 mm	545 mm	600 mm	345 mm	15,40 kg	259,5 mm
41	1,11 kg	1,45 kg	260 mm	320 mm	120 mm	545 mm	600 mm	345 mm	15,80 kg	267,0 mm
42	1,17 kg	1,48 kg	260 mm	320 mm	120 mm	545 mm	600 mm	345 mm	16,20 kg	274,5 mm
43	1,24 kg	1,59 kg	275 mm	350 mm	125 mm	575 mm	650 mm	375 mm	17,40 kg	282,0 mm
44	1,25 kg	1,61 kg	275 mm	350 mm	125 mm	575 mm	650 mm	375 mm	17,60 kg	289,5 mm
45	1,32 kg	1,69 kg	275 mm	350 mm	125 mm	575 mm	650 mm	375 mm	18,40 kg	297,0 mm
46	1,42 kg	1,78 kg	275 mm	350 mm	125 mm	575 mm	650 mm	375 mm	19,00 kg	304,5 mm
47	1,42 kg	1,81 kg	275 mm	350 mm	125 mm	575 mm	650 mm	375 mm	19,40 kg	312,0 mm
48	1,55 kg	1,91 kg	275 mm	350 mm	125 mm	575 mm	650 mm	375 mm	19,80 kg	319,5 mm

Business parameters

Tarric	64039113
Country	CN
Weight	1,47 kg
Add Unit	NPR
Add Quantity	1