

ONTARIO low cut outdoor shoes red

» Shoes » Outdoor shoes » Low cut

Technical sheet

ONTARIO low cut outdoor shoes red

Product code: 4405-35



upper	breathable, abrasion-resistant textile
lining	SOFT LINNER – stretch, breathable with absorption capability
inner insole	HI-POLY – anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
outsole	EVA/RUBBER – glued construction
size	36 – 48
usability	shoes suitable for daily wear and outdoor activities
version	red colour

Properties

PL Midsole penetration protection nonmetallic - PL	No
PS Midsole penetration protection nonmetallic - PS	No
SR Antislip prop. on ceramic with glycerol	No
WPA Water resistant upper	No
HRO Resist. of the outsole against contact heat	No
WR Water resistant	No
WRU Water resistant upper	No

ONTARIO low cut outdoor shoes red

» Shoes » Outdoor shoes » Low cut

CI Insulation against cold	No
HI Insulation of the outsole against heat	No
FO Resist. of the outsole against fuel oils	No
P Midsole penetration protection	No
E Energy absorption in the heel area	No
M Instep protection	No
A Antistatic properties	No
AN Ankle protection	No
CR Cut resistant upper	No
SRA Antislip prop. on ceramic tile with SLS	No
SRB Antislip prop. on smooth steel with glycerol	No
SRC Antislip resistance SRA + SRB	No
Free-tex Membrane	No
Michelin Michelin® sole	No
BOA BOA Fit System	No
NON-METALIC Footwear without metal parts	No
ESD antistatic properties ESD	No
Winter Winter footwear	No
ANTICUT Anti-cut boots	No

Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
36	0,45 kg	0,66 kg	200 mm	320 mm	115 mm	425 mm	605 mm	340 mm	7,80 kg	240,0 mm
37	0,47 kg	0,68 kg	200 mm	320 mm	115 mm	425 mm	605 mm	340 mm	8,00 kg	247,0 mm
38	0,49 kg	0,69 kg	200 mm	320 mm	115 mm	425 mm	605 mm	340 mm	8,20 kg	253,0 mm
39	0,51 kg	0,72 kg	200 mm	320 mm	115 mm	425 mm	605 mm	340 mm	8,40 kg	260,0 mm
40	0,56 kg	0,81 kg	200 mm	320 mm	115 mm	425 mm	605 mm	340 mm	8,60 kg	267,0 mm
41	0,57 kg	0,81 kg	200 mm	320 mm	115 mm	425 mm	605 mm	340 mm	8,80 kg	273,0 mm
42	0,58 kg	0,83 kg	220 mm	370 mm	125 mm	470 mm	650 mm	400 mm	9,80 kg	280,0 mm
43	0,60 kg	0,85 kg	220 mm	370 mm	125 mm	470 mm	650 mm	400 mm	10,00 kg	286,0 mm
44	0,64 kg	0,90 kg	220 mm	370 mm	125 mm	470 mm	650 mm	400 mm	10,40 kg	293,0 mm
45	0,68 kg	0,94 kg	220 mm	370 mm	125 mm	470 mm	650 mm	400 mm	10,80 kg	300,0 mm
46	0,73 kg	0,97 kg	220 mm	370 mm	125 mm	470 mm	650 mm	400 mm	11,00 kg	306,0 mm
47	0,74 kg	0,99 kg	220 mm	370 mm	125 mm	470 mm	650 mm	400 mm	11,20 kg	313,0 mm
48	0,75 kg	1,01 kg	220 mm	370 mm	125 mm	470 mm	650 mm	400 mm	11,40 kg	320,0 mm

Business parameters

Tarric	64041990
Country	BD
Weight	0,81 kg
Add Unit	NPR
Add Quantity	1