

# NOTTINGHAM occupational boots

» Shoes » Occupational shoes » Boots

## Technical sheet

### NOTTINGHAM occupational boots

Product code: 6570-02



<b>upper</b>	abrasion resistant textile material OXFORD
<b>lining</b>	breathable thermo-insulation MEMBRANE FREE-TEX®
<b>inner insole</b>	expanded polyurethane of high absorbency, antistatic
<b>outsole</b>	EVA/RUBBER – antistatic, glued construction
<b>size</b>	39 – 47
<b>standard</b>	EN ISO 20347:2012
<b>version</b>	O2 WR CI SRA – without composite toe cap and kevlar midsole, hydrophobic, FREE-TEX®

## Properties

<b>PL</b> Midsole penetration protection nonmetallic - PL	No
<b>PS</b> Midsole penetration protection nonmetallic - PS	No
<b>SR</b> Antislip prop. on ceramic with glycerol	No
<b>WPA</b> Water resistant upper	No
<b>HRO</b> Resist. of the outsole against contact heat	No
<b>WR</b> Water resistant	Yes
<b>WRU</b> Water resistant upper	Yes

# NOTTINGHAM occupational boots

» Shoes » Occupational shoes » Boots

<b>CI</b> Insulation against cold	Yes
<b>HI</b> Insulation of the outsole against heat	No
<b>FO</b> Resist. of the outsole against fuel oils	No
<b>P</b> Midsole penetration protection	No
<b>E</b> Energy absorption in the heel area	No
<b>M</b> Instep protection	No
<b>A</b> Antistatic properties	No
<b>AN</b> Ankle protection	No
<b>CR</b> Cut resistant upper	No
<b>SRA</b> Antislip prop. on ceramic tile with SLS	Yes
<b>SRB</b> Antislip prop. on smooth steel with glycerol	No
<b>SRC</b> Antislip resistance SRA + SRB	No
<b>Free-tex</b> Membrane	Yes
<b>Michelin</b> Michelin® sole	No
<b>BOA</b> BOA Fit System	No
<b>NON-METALIC</b> Footwear without metal parts	No
<b>ESD</b> antistatic properties ESD	No
<b>Winter</b> Winter footwear	No
<b>ANTICUT</b> Anti-cut boots	No
<b>Standard</b>	20347:2012
<b>Shoe marking</b>	O2

## Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
36	1,01 kg	1,36 kg	310 mm	330 mm	120 mm	620 mm	635 mm	355 mm	14,80 kg	0,0 mm
37	1,03 kg	1,39 kg	310 mm	330 mm	120 mm	620 mm	635 mm	355 mm	15,00 kg	0,0 mm
38	1,09 kg	1,44 kg	310 mm	330 mm	120 mm	620 mm	635 mm	355 mm	15,20 kg	0,0 mm
39	1,18 kg	1,54 kg	310 mm	335 mm	125 mm	630 mm	640 mm	360 mm	16,80 kg	0,0 mm
40	1,20 kg	1,56 kg	310 mm	335 mm	125 mm	630 mm	640 mm	360 mm	17,20 kg	0,0 mm
41	1,25 kg	1,61 kg	310 mm	335 mm	125 mm	630 mm	640 mm	360 mm	17,40 kg	0,0 mm
42	1,31 kg	1,67 kg	310 mm	335 mm	125 mm	630 mm	640 mm	360 mm	18,00 kg	0,0 mm
43	1,35 kg	1,77 kg	330 mm	365 mm	135 mm	685 mm	710 mm	390 mm	19,60 kg	0,0 mm
44	1,40 kg	1,82 kg	330 mm	365 mm	135 mm	685 mm	710 mm	390 mm	19,80 kg	0,0 mm
45	1,44 kg	1,86 kg	330 mm	365 mm	135 mm	685 mm	710 mm	390 mm	20,20 kg	0,0 mm
46	1,48 kg	1,90 kg	330 mm	365 mm	135 mm	685 mm	710 mm	390 mm	20,60 kg	0,0 mm
47	1,55 kg	1,97 kg	330 mm	365 mm	135 mm	685 mm	710 mm	390 mm	21,40 kg	0,0 mm

## Business parameters

<b>Tarric</b>	64041990
<b>Country</b>	CN
<b>Weight</b>	1,50 kg
<b>Add Unit</b>	NPR
<b>Add Quantity</b>	1