

OKLAHOMA low cut occupational shoes

» Shoes » Occupational shoes » Low cut

Technical sheet

OKLAHOMA low cut occupational shoes

Product code: 4385-02



upper	cowhide leather NUBUCK in a thickness of 1,9 – 2,1 mm
lining	breathable thermo-insulation MEMBRANE FREE-TEX®
inner insole	HI-POLY – anatomically shaped lightweight polyurethane foam coated with fabric MESH, antistatic
outsole	MICHELIN EVA/RUBBER – resistant to fuel oils, antistatic, antislip, glued construction
size	38 – 49
standard	EN ISO 20347:2012
version	O2 FO SRA – without steel toe cap, hydrophobic, FREE-TEX®

Properties

PL Midsole penetration protection nonmetallic - PL	No
PS Midsole penetration protection nonmetallic - PS	No
SR Antislip prop. on ceramic with glycerol	No
WPA Water resistant upper	No
HRO Resist. of the outsole against contact heat	No
WR Water resistant	No

OKLAHOMA low cut occupational shoes

» Shoes » Occupational shoes » Low cut

WRU Water resistant upper	Yes
CI Insulation against cold	No
HI Insulation of the outsole against heat	No
FO Resist. of the outsole against fuel oils	Yes
P Midsole penetration protection	No
E Energy absorption in the heel area	Yes
M Instep protection	No
A Antistatic properties	Yes
AN Ankle protection	No
CR Cut resistant upper	No
SRA Antislip prop. on ceramic tile with SLS	Yes
SRB Antislip prop. on smooth steel with glycerol	Yes
SRC Antislip resistance SRA + SRB	Yes
Free-tex Membrane	Yes
Michelin Michelin® sole	Yes
BOA BOA Fit System	No
NON-METALIC Footwear without metal parts	No
ESD antistatic properties ESD	No
Winter Winter footwear	No
ANTICUT Anti-cut boots	No
Standard	20347:2012
Shoe marking	O2

Logistics parameters

Velikost	Net weight	Gross weight	Sales box - widht	Sales box - length	Sales box - height	Group packaging - widht	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
38	0,93 kg	1,19 kg	230 mm	330 mm	120 mm	480 mm	620 mm	350 mm	13,60 kg	0,0 mm
39	1,00 kg	1,16 kg	230 mm	330 mm	120 mm	480 mm	620 mm	350 mm	13,80 kg	0,0 mm
40	1,03 kg	1,31 kg	230 mm	330 mm	120 mm	480 mm	620 mm	350 mm	14,00 kg	0,0 mm
41	1,04 kg	1,32 kg	230 mm	330 mm	120 mm	480 mm	620 mm	350 mm	14,40 kg	0,0 mm
42	1,08 kg	1,36 kg	230 mm	330 mm	120 mm	480 mm	620 mm	350 mm	14,60 kg	0,0 mm
43	1,15 kg	1,41 kg	240 mm	360 mm	125 mm	500 mm	640 mm	385 mm	15,60 kg	0,0 mm
44	1,16 kg	1,42 kg	240 mm	360 mm	125 mm	500 mm	640 mm	385 mm	15,80 kg	0,0 mm
45	1,17 kg	1,49 kg	240 mm	360 mm	125 mm	500 mm	640 mm	385 mm	16,40 kg	0,0 mm
46	1,19 kg	1,57 kg	240 mm	360 mm	125 mm	500 mm	640 mm	385 mm	16,60 kg	0,0 mm
47	1,23 kg	1,55 kg	240 mm	360 mm	125 mm	500 mm	640 mm	385 mm	16,80 kg	0,0 mm

Business parameters

Tarric	64039993
Country	CN
Weight	1,29 kg
Add Unit	NPR
Add Quantity	1