

OHIO low cut safety shoes

» Shoes » Safety shoes » Low cut

Technical sheet

OHIO low cut safety shoes

Product code: 4855-S1



upper	technologically advanced SOFTSHELL material
lining	laminated breathable fabric MESH
inner insole	HI-POLY – anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
outsole	MICHELIN EVA/RUBBER – resistant to fuel oils, antistatic, antislip
size	39 – 47
standard	EN ISO 20345:2011
version	S1 SRC – with composite toe cap

Properties

PL Midsole penetration protection nonmetallic - PL	No
PS Midsole penetration protection nonmetallic - PS	No
SR Antislip prop. on ceramic with glycerol	No
WPA Water resistant upper	No
HRO Resist. of the outsole against contact heat	No
WR Water resistant	No
WRU Water resistant upper	No

OHIO low cut safety shoes

» Shoes » Safety shoes » Low cut

CI Insulation against cold	No
HI Insulation of the outsole against heat	No
FO Resist. of the outsole against fuel oils	Yes
P Midsole penetration protection	No
E Energy absorption in the heel area	Yes
M Instep protection	No
A Antistatic properties	Yes
AN Ankle protection	No
CR Cut resistant upper	No
SRA Antislip prop. on ceramic tile with SLS	Yes
SRB Antislip prop. on smooth steel with glycerol	Yes
SRC Antislip resistance SRA + SRB	Yes
Free-tex Membrane	No
Michelin Michelin® sole	Yes
BOA BOA Fit System	No
NON-METALIC Footwear without metal parts	No
ESD antistatic properties ESD	No
Winter Winter footwear	No
ANTICUT Anti-cut boots	No
Standard	20345:2012
Shoe marking	S1

Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
39	1,03 kg	1,31 kg	230 mm	330 mm	120 mm	480 mm	625 mm	355 mm	14,40 kg	0,0 mm
40	1,08 kg	1,36 kg	230 mm	330 mm	120 mm	480 mm	625 mm	355 mm	14,60 kg	0,0 mm
41	1,11 kg	1,40 kg	230 mm	330 mm	120 mm	480 mm	625 mm	355 mm	15,20 kg	0,0 mm
42	1,17 kg	1,46 kg	230 mm	330 mm	120 mm	480 mm	625 mm	355 mm	15,80 kg	0,0 mm
43	1,23 kg	1,52 kg	230 mm	330 mm	120 mm	480 mm	625 mm	355 mm	16,00 kg	0,0 mm
44	1,29 kg	1,61 kg	255 mm	350 mm	125 mm	535 mm	655 mm	380 mm	17,40 kg	0,0 mm
45	1,35 kg	1,67 kg	255 mm	350 mm	125 mm	535 mm	655 mm	380 mm	17,80 kg	0,0 mm
46	1,37 kg	1,69 kg	255 mm	350 mm	125 mm	535 mm	655 mm	380 mm	18,20 kg	0,0 mm
47	1,41 kg	1,74 kg	255 mm	350 mm	125 mm	535 mm	655 mm	380 mm	18,60 kg	0,0 mm

Business parameters

Tarric	64041990
Country	CN
Weight	1,31 kg
Add Unit	NPR
Add Quantity	1