

MARIBOR safety sandal

» Shoes » Safety shoes » Sandals

Technical sheet

MARIBOR safety sandal



Product code: 2265-S1NON



upper	brushed cow suede leather, coated in a thickness of 1,8 – 2,0 mm
lining	laminated breathable fabric MESH
inner insole	HI-POLY – anatomically shaped lightweight polyurethane foam coated with fabric MESH, antistatic
outsole	PU/PU – resistant to fuel oils, antistatic, antislip, double density injection
size	36 – 48
standard	EN ISO 20345:2011
version	S1 SRA – with composite toe cap, NON METALLIC

Properties

PL Midsole penetration protection nonmetallic - PL	No
PS Midsole penetration protection nonmetallic - PS	No
SR Antislip prop. on ceramic with glycerol	No
WPA Water resistant upper	No
HRO Resist. of the outsole against contact heat	No
WR Water resistant	No
WRU Water resistant upper	No

MARIBOR safety sandal

» Shoes » Safety shoes » Sandals

CI	Insulation against cold	No
HI	Insulation of the outsole against heat	No
FO	Resist. of the outsole against fuel oils	Yes
P	Midsole penetration protection	No
E	Energy absorption in the heel area	Yes
M	Instep protection	No
A	Antistatic properties	Yes
AN	Ankle protection	No
CR	Cut resistant upper	No
SRA	Antislip prop. on ceramic tile with SLS	Yes
SRB	Antislip prop. on smooth steel with glycerol	No
SRC	Antislip resistance SRA + SRB	No
Free-tex	Membrane	No
Michelin	Michelin® sole	No
BOA	BOA Fit System	No
NON-METALIC	Footwear without metal parts	Yes
ESD	antistatic properties ESD	No
Winter	Winter footwear	No
ANTICUT	Anti-cut boots	No
Standard		20345:2012
Shoe marking		S1

Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
36	0,74 kg	0,97 kg	200 mm	311 mm	120 mm	420 mm	600 mm	330 mm	10,40 kg	231,0 mm
37	0,76 kg	1,00 kg	200 mm	311 mm	120 mm	420 mm	600 mm	330 mm	10,80 kg	237,7 mm
38	0,79 kg	1,02 kg	200 mm	311 mm	120 mm	420 mm	600 mm	330 mm	11,00 kg	244,3 mm
39	0,82 kg	1,06 kg	200 mm	311 mm	120 mm	420 mm	600 mm	330 mm	11,40 kg	251,0 mm
40	0,84 kg	1,08 kg	200 mm	311 mm	120 mm	420 mm	600 mm	330 mm	11,80 kg	257,7 mm
41	0,86 kg	1,10 kg	200 mm	311 mm	120 mm	420 mm	600 mm	330 mm	11,80 kg	264,3 mm
42	0,89 kg	1,13 kg	200 mm	311 mm	120 mm	420 mm	600 mm	330 mm	12,00 kg	271,0 mm
43	0,93 kg	1,19 kg	204 mm	330 mm	120 mm	430 mm	620 mm	350 mm	12,60 kg	277,7 mm
44	0,97 kg	1,23 kg	204 mm	330 mm	120 mm	430 mm	620 mm	350 mm	13,20 kg	284,3 mm
45	1,01 kg	1,26 kg	204 mm	330 mm	120 mm	430 mm	620 mm	350 mm	13,40 kg	291,0 mm
46	1,02 kg	1,30 kg	210 mm	350 mm	125 mm	440 mm	650 mm	370 mm	13,80 kg	299,7 mm
47	1,08 kg	1,35 kg	210 mm	350 mm	125 mm	440 mm	650 mm	370 mm	14,40 kg	304,4 mm
48	1,09 kg	1,36 kg	210 mm	350 mm	125 mm	440 mm	650 mm	370 mm	14,60 kg	311,0 mm

Business parameters

Tarric	64034000
Country	CN
Weight	1,14 kg
Add Unit	NPR

MARIBOR safety sandal

» Shoes » Safety shoes » Sandals

Add Quantity 1