

MADISON low cut safety shoes

» Shoes » Safety shoes » Low cut

Technical sheet

MADISON low cut safety shoes

Product code: 2595-S1



upper	dry mild cowhide leather NUBUCK in a thickness of 1,8 – 2,0 mm
lining	laminated breathable fabric MESH
inner insole	HI-POLY – padded, anatomically shaped, made of porous polyurethane foam, coated with fabric MESH, antistatic
outsole	PU/PU – resistant to fuel oils, antistatic, antislip, double density injection
size	39 – 47
standard	EN ISO 20345:2011
version	S1 FO SRA – with steel toe cap

Properties

PL Midsole penetration protection nonmetallic - PL	No
PS Midsole penetration protection nonmetallic - PS	No
SR Antislip prop. on ceramic with glycerol	No
WPA Water resistant upper	No
HRO Resist. of the outsole against contact heat	No
WR Water resistant	No
WRU Water resistant upper	No

MADISON low cut safety shoes

» Shoes » Safety shoes » Low cut

CI Insulation against cold	No
HI Insulation of the outsole against heat	No
FO Resist. of the outsole against fuel oils	Yes
P Midsole penetration protection	No
E Energy absorption in the heel area	Yes
M Instep protection	No
A Antistatic properties	Yes
AN Ankle protection	No
CR Cut resistant upper	No
SRA Antislip prop. on ceramic tile with SLS	Yes
SRB Antislip prop. on smooth steel with glycerol	No
SRC Antislip resistance SRA + SRB	No
Free-tex Membrane	No
Michelin Michelin® sole	No
BOA BOA Fit System	No
NON-METALIC Footwear without metal parts	No
ESD antistatic properties ESD	No
Winter Winter footwear	No
ANTICUT Anti-cut boots	No
Standard	20345:2012
Shoe marking	S1

Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
39	0,98 kg	1,32 kg	220 mm	325 mm	125 mm	470 mm	630 mm	335 mm	14,80 kg	0,0 mm
40	1,03 kg	1,38 kg	220 mm	325 mm	125 mm	470 mm	630 mm	335 mm	15,20 kg	0,0 mm
41	1,09 kg	1,45 kg	220 mm	325 mm	125 mm	470 mm	630 mm	335 mm	15,80 kg	0,0 mm
42	1,15 kg	1,51 kg	220 mm	325 mm	125 mm	470 mm	630 mm	335 mm	16,20 kg	0,0 mm
43	1,16 kg	1,55 kg	230 mm	345 mm	125 mm	480 mm	650 mm	365 mm	17,00 kg	0,0 mm
44	1,21 kg	1,60 kg	230 mm	345 mm	125 mm	480 mm	650 mm	365 mm	17,60 kg	0,0 mm
45	1,27 kg	1,69 kg	230 mm	345 mm	125 mm	480 mm	650 mm	365 mm	18,20 kg	0,0 mm
46	1,27 kg	1,69 kg	230 mm	345 mm	125 mm	480 mm	650 mm	365 mm	18,60 kg	0,0 mm
47	1,31 kg	1,69 kg	230 mm	345 mm	125 mm	480 mm	650 mm	365 mm	18,80 kg	0,0 mm

Business parameters

Tarric	64034000
Country	CN
Weight	1,40 kg
Add Unit	NPR
Add Quantity	1