


LIMA low cut occupational shoes

» Shoes » Occupational shoes » Low cut

Technical sheet

LIMA low cut occupational shoes

Product code: 4115-OB



upper	cowhide leather NUBUCK in a thickness of 1,9 – 2,1 mm
lining	breathable thermo-insulation MEMBRANE FREE-TEX®
inner insole	HI-POLY – anatomically shaped lightweight polyurethane foam coated with fabric MESH, antistatic
outsole	EVA/RUBBER – antistatic, antislip, glued construction
size	36 – 49
standard	EN ISO 20347:2012
version	OB E WRU SRA – without steel toe cap, hydrophobic, FREE-TEX®

Properties

PL Midsole penetration protection nonmetallic - PL	No
PS Midsole penetration protection nonmetallic - PS	No
SR Antislip prop. on ceramic with glycerol	No
WPA Water resistant upper	No
HRO Resist. of the outsole against contact heat	No
WR Water resistant	No
WRU Water resistant upper	Yes

LIMA low cut occupational shoes

» Shoes » Occupational shoes » Low cut

CI Insulation against cold	No
HI Insulation of the outsole against heat	No
FO Resist. of the outsole against fuel oils	No
P Midsole penetration protection	No
E Energy absorption in the heel area	Yes
M Instep protection	No
A Antistatic properties	No
AN Ankle protection	No
CR Cut resistant upper	No
SRA Antislip prop. on ceramic tile with SLS	Yes
SRB Antislip prop. on smooth steel with glycerol	No
SRC Antislip resistance SRA + SRB	No
Free-tex Membrane	Yes
Michelin Michelin® sole	No
BOA BOA Fit System	No
NON-METALIC Footwear without metal parts	No
ESD antistatic properties ESD	No
Winter Winter footwear	No
ANTICUT Anti-cut boots	No
Standard	20347:2012
Shoe marking	OB

Logistics parameters

Velikost	Net weight	Gross weight	Sales box - widht	Sales box - length	Sales box - height	Group packaging - widht	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
36	0,92 kg	1,20 kg	230 mm	330 mm	120 mm	490 mm	630 mm	350 mm	13,20 kg	0,0 mm
37	0,94 kg	1,22 kg	230 mm	330 mm	120 mm	490 mm	630 mm	350 mm	13,40 kg	0,0 mm
38	0,96 kg	1,25 kg	230 mm	330 mm	120 mm	490 mm	630 mm	350 mm	13,60 kg	0,0 mm
39	1,03 kg	1,31 kg	230 mm	330 mm	120 mm	490 mm	630 mm	350 mm	13,90 kg	0,0 mm
40	1,06 kg	1,34 kg	230 mm	330 mm	120 mm	490 mm	630 mm	350 mm	14,40 kg	0,0 mm
41	1,07 kg	1,40 kg	255 mm	350 mm	125 mm	535 mm	640 mm	370 mm	15,20 kg	0,0 mm
42	1,18 kg	1,49 kg	255 mm	350 mm	125 mm	535 mm	640 mm	370 mm	16,00 kg	0,0 mm
43	1,20 kg	1,52 kg	255 mm	350 mm	125 mm	535 mm	640 mm	370 mm	16,60 kg	0,0 mm
44	1,24 kg	1,56 kg	255 mm	350 mm	125 mm	535 mm	640 mm	370 mm	17,00 kg	0,0 mm
45	1,28 kg	1,61 kg	260 mm	370 mm	130 mm	545 mm	670 mm	395 mm	17,40 kg	0,0 mm
46	1,34 kg	1,68 kg	260 mm	370 mm	130 mm	545 mm	670 mm	395 mm	18,00 kg	0,0 mm
47	1,40 kg	1,74 kg	260 mm	370 mm	130 mm	545 mm	670 mm	395 mm	18,60 kg	0,0 mm
48	1,41 kg	1,75 kg	260 mm	370 mm	130 mm	545 mm	670 mm	395 mm	18,80 kg	0,0 mm
49	1,50 kg	1,84 kg	260 mm	370 mm	130 mm	545 mm	670 mm	395 mm	20,00 kg	0,0 mm

Business parameters

Tarric	64039993
Country	CN
Weight	1,43 kg
Add Unit	NPR

LIMA low cut occupational shoes

» Shoes » Occupational shoes » Low cut

Add Quantity 1