

HOUSTON high heel safety shoes

» Shoes » Safety shoes » Boots

Technical sheet

HOUSTON high heel safety shoes

Product code: 5490-S3



upper	smooth cowhide leather in a thickness of 2,0 - 2,2 mm
lining	breathable thermo-insulation MEMBRANE FREE-TEX®
inner insole	anatomically shaped from material EVA with a high absorbency, antistatic
outsole	PU/RUBBER - up to 300°C, resistant to fuel oils, antistatic, antislip, double density injection
size	36 - 48
standard	EN ISO 20345:2011
version	S3 HRO SRC WR CI - with composite toe cap and kevlar midsole, hydrophobic FREE-TEX®

Properties

PL Midsole penetration protection nonmetallic - PL	No
PS Midsole penetration protection nonmetallic - PS	No
SR Antislip prop. on ceramic with glycerol	No
WPA Water resistant upper	No
HRO Resist. of the outsole against contact heat	Yes
WR Water resistant	Yes

HOUSTON high heel safety shoes

» Shoes » Safety shoes » Boots

WRU Water resistant upper	Yes
CI Insulation against cold	Yes
HI Insulation of the outsole against heat	No
FO Resist. of the outsole against fuel oils	Yes
P Midsole penetration protection	Yes
E Energy absorption in the heel area	Yes
M Instep protection	No
A Antistatic properties	Yes
AN Ankle protection	No
CR Cut resistant upper	No
SRA Antislip prop. on ceramic tile with SLS	Yes
SRB Antislip prop. on smooth steel with glycerol	Yes
SRC Antislip resistance SRA + SRB	Yes
Free-tex Membrane	Yes
Michelin Michelin® sole	No
BOA BOA Fit System	No
NON-METALIC Footwear without metal parts	No
ESD antistatic properties ESD	No
Winter Winter footwear	No
ANTICUT Anti-cut boots	No
Standard	20345:2012
Shoe marking	S3

Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
36	1,31 kg	1,67 kg	325 mm	330 mm	120 mm	600 mm	650 mm	345 mm	18,20 kg	233,0 mm
37	1,31 kg	1,68 kg	325 mm	330 mm	120 mm	600 mm	650 mm	345 mm	18,40 kg	239,7 mm
38	1,32 kg	1,68 kg	325 mm	330 mm	120 mm	600 mm	650 mm	345 mm	18,50 kg	246,3 mm
39	1,42 kg	1,74 kg	325 mm	330 mm	120 mm	600 mm	650 mm	345 mm	18,60 kg	253,0 mm
40	1,45 kg	1,76 kg	325 mm	330 mm	120 mm	600 mm	650 mm	345 mm	19,00 kg	259,7 mm
41	1,53 kg	1,85 kg	325 mm	330 mm	120 mm	600 mm	650 mm	345 mm	19,60 kg	266,3 mm
42	1,55 kg	1,86 kg	325 mm	330 mm	120 mm	600 mm	650 mm	345 mm	19,80 kg	273,0 mm
43	1,57 kg	1,90 kg	325 mm	330 mm	125 mm	620 mm	660 mm	355 mm	20,20 kg	279,7 mm
44	1,64 kg	1,97 kg	325 mm	330 mm	125 mm	620 mm	660 mm	355 mm	21,00 kg	286,3 mm
45	1,67 kg	2,01 kg	325 mm	330 mm	125 mm	620 mm	660 mm	355 mm	21,40 kg	293,0 mm
46	1,79 kg	2,16 kg	340 mm	350 mm	130 mm	650 mm	685 mm	375 mm	23,00 kg	299,7 mm
47	1,88 kg	2,22 kg	340 mm	350 mm	130 mm	650 mm	685 mm	375 mm	23,40 kg	306,4 mm
48	1,91 kg	2,28 kg	340 mm	350 mm	130 mm	650 mm	685 mm	375 mm	23,60 kg	313,0 mm

Business parameters

Tarric	64034000
Country	CN
Weight	1,90 kg

HOUSTON high heel safety shoes

» Shoes » Safety shoes » Boots

Add Unit	NPR
Add Quantity	1