

# IOWA low cut occupational shoes

» Shoes » Occupational shoes » Low cut

## Technical sheet

### IOWA low cut occupational shoes

Product code: 4745-01



|                     |                                                                                                 |
|---------------------|-------------------------------------------------------------------------------------------------|
| <b>upper</b>        | brushed cow suede leather VELOUR in a combination with textile in a thickness of 1,5 - 1,7 mm   |
| <b>lining</b>       | laminated breathable fabric MESH                                                                |
| <b>inner insole</b> | HI-POLY - anatomically shaped lightweight polyurethane foam coated with fabric MESH, antistatic |
| <b>outsole</b>      | EVA/RUBBER - glued construction                                                                 |
| <b>size</b>         | 36 - 48                                                                                         |
| <b>standard</b>     | EN ISO 20347:2012                                                                               |
| <b>version</b>      | 01 FO SRA - without steel toe cap                                                               |

## Properties

|                                                           |    |
|-----------------------------------------------------------|----|
| <b>PL</b> Midsole penetration protection nonmetallic - PL | No |
| <b>PS</b> Midsole penetration protection nonmetallic - PS | No |
| <b>SR</b> Antislip prop. on ceramic with glycerol         | No |
| <b>WPA</b> Water resistant upper                          | No |
| <b>HRO</b> Resist. of the outsole against contact heat    | No |
| <b>WR</b> Water resistant                                 | No |

# IOWA low cut occupational shoes

» Shoes » Occupational shoes » Low cut

|                                                         |            |
|---------------------------------------------------------|------------|
| <b>WRU</b> Water resistant upper                        | No         |
| <b>CI</b> Insulation against cold                       | No         |
| <b>HI</b> Insulation of the outsole against heat        | No         |
| <b>FO</b> Resist. of the outsole against fuel oils      | Yes        |
| <b>P</b> Midsole penetration protection                 | No         |
| <b>E</b> Energy absorption in the heel area             | Yes        |
| <b>M</b> Instep protection                              | No         |
| <b>A</b> Antistatic properties                          | Yes        |
| <b>AN</b> Ankle protection                              | No         |
| <b>CR</b> Cut resistant upper                           | No         |
| <b>SRA</b> Antislip prop. on ceramic tile with SLS      | Yes        |
| <b>SRB</b> Antislip prop. on smooth steel with glycerol | No         |
| <b>SRC</b> Antislip resistance SRA + SRB                | No         |
| <b>Free-tex</b> Membrane                                | No         |
| <b>Michelin</b> Michelin® sole                          | No         |
| <b>BOA</b> BOA Fit System                               | No         |
| <b>NON-METALIC</b> Footwear without metal parts         | No         |
| <b>ESD</b> antistatic properties ESD                    | No         |
| <b>Winter</b> Winter footwear                           | No         |
| <b>ANTICUT</b> Anti-cut boots                           | No         |
| <b>Standard</b>                                         | 20347:2012 |
| <b>Shoe marking</b>                                     | O1         |

## Logistics parameters

| Velikost | Net weight | Gross weight | Sales box - width | Sales box - length | Sales box - height | Group packaging - width | Group packaging - length | Group packaging - height | Group packaging - weight | Vnitřní délka obuvi |
|----------|------------|--------------|-------------------|--------------------|--------------------|-------------------------|--------------------------|--------------------------|--------------------------|---------------------|
| 37       | 0,00 kg    | 0,00 kg      | 0 mm              | 0 mm               | 0 mm               | 0 mm                    | 0 mm                     | 0 mm                     | 0,00 kg                  | 243,0 mm            |
| 38       | 0,00 kg    | 0,00 kg      | 0 mm              | 0 mm               | 0 mm               | 0 mm                    | 0 mm                     | 0 mm                     | 0,00 kg                  | 250,0 mm            |
| 39       | 0,84 kg    | 1,16 kg      | 210 mm            | 320 mm             | 115 mm             | 455 mm                  | 610 mm                   | 345 mm                   | 12,80 kg                 | 257,0 mm            |
| 40       | 0,90 kg    | 1,26 kg      | 230 mm            | 320 mm             | 120 mm             | 500 mm                  | 640 mm                   | 355 mm                   | 13,60 kg                 | 263,0 mm            |
| 41       | 0,93 kg    | 1,29 kg      | 230 mm            | 320 mm             | 120 mm             | 500 mm                  | 640 mm                   | 355 mm                   | 14,20 kg                 | 270,0 mm            |
| 42       | 0,95 kg    | 1,34 kg      | 250 mm            | 340 mm             | 130 mm             | 535 mm                  | 685 mm                   | 370 mm                   | 15,00 kg                 | 276,0 mm            |
| 43       | 0,98 kg    | 1,37 kg      | 250 mm            | 340 mm             | 130 mm             | 535 mm                  | 685 mm                   | 370 mm                   | 15,40 kg                 | 283,0 mm            |
| 44       | 1,00 kg    | 1,40 kg      | 250 mm            | 340 mm             | 130 mm             | 535 mm                  | 685 mm                   | 370 mm                   | 15,60 kg                 | 289,0 mm            |
| 45       | 1,04 kg    | 1,47 kg      | 250 mm            | 340 mm             | 130 mm             | 535 mm                  | 685 mm                   | 370 mm                   | 16,60 kg                 | 296,0 mm            |
| 46       | 1,09 kg    | 1,50 kg      | 270 mm            | 370 mm             | 130 mm             | 575 mm                  | 695 mm                   | 405 mm                   | 17,00 kg                 | 303,0 mm            |
| 47       | 1,12 kg    | 1,53 kg      | 270 mm            | 370 mm             | 130 mm             | 575 mm                  | 695 mm                   | 405 mm                   | 17,20 kg                 | 310,0 mm            |
| 48       | 1,16 kg    | 1,58 kg      | 270 mm            | 370 mm             | 130 mm             | 575 mm                  | 695 mm                   | 405 mm                   | 17,80 kg                 | 316,0 mm            |

## Business parameters

|                 |          |
|-----------------|----------|
| <b>Tarric</b>   | 64039993 |
| <b>Country</b>  | CN       |
| <b>Weight</b>   | 1,43 kg  |
| <b>Add Unit</b> | NPR      |

# IOWA low cut occupational shoes

» Shoes » Occupational shoes » Low cut

**Add Quantity**    1