

LISABON ankle safety shoes

» Shoes » Safety shoes » Ankle

Technical sheet

LISABON ankle safety shoes

Product code: 2660-S1



upper	brushed cowhide suede leather VELOUR in a thickness of 1,7 - 1,9 mm
lining	laminated breathable fabric MESH
inner insole	anatomically shaped from material EVA with a high absorbency, antistatic
outsole	PU/PU - transparent - resistant to fuel oils, antistatic, antislip, double density injection
size	36 - 48
standard	EN ISO 20345:2011
version	S1 SRC - with steel toe cap

Properties

PL Midsole penetration protection nonmetallic - PL	No
PS Midsole penetration protection nonmetallic - PS	No
SR Antislip prop. on ceramic with glycerol	No
WPA Water resistant upper	No
HRO Resist. of the outsole against contact heat	No
WR Water resistant	No
WRU Water resistant upper	No

LISABON ankle safety shoes

» Shoes » Safety shoes » Ankle

CI Insulation against cold	No
HI Insulation of the outsole against heat	No
FO Resist. of the outsole against fuel oils	Yes
P Midsole penetration protection	No
E Energy absorption in the heel area	Yes
M Instep protection	No
A Antistatic properties	Yes
AN Ankle protection	No
CR Cut resistant upper	No
SRA Antislip prop. on ceramic tile with SLS	Yes
SRB Antislip prop. on smooth steel with glycerol	Yes
SRC Antislip resistance SRA + SRB	Yes
Free-tex Membrane	No
Michelin Michelin® sole	No
BOA BOA Fit System	No
NON-METALIC Footwear without metal parts	No
ESD antistatic properties ESD	No
Winter Winter footwear	No
ANTICUT Anti-cut boots	No
Standard	20345:2012
Shoe marking	S1

Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
36	1,13 kg	1,42 kg	225 mm	315 mm	115 mm	470 mm	590 mm	340 mm	16,20 kg	244,0 mm
37	1,18 kg	1,47 kg	225 mm	315 mm	115 mm	470 mm	590 mm	340 mm	16,40 kg	251,0 mm
38	1,26 kg	1,55 kg	225 mm	315 mm	115 mm	470 mm	590 mm	340 mm	17,00 kg	257,0 mm
39	1,30 kg	1,58 kg	225 mm	315 mm	115 mm	470 mm	590 mm	340 mm	17,40 kg	264,0 mm
40	1,32 kg	1,61 kg	225 mm	315 mm	115 mm	470 mm	590 mm	340 mm	17,60 kg	271,0 mm
41	1,39 kg	1,66 kg	225 mm	315 mm	115 mm	470 mm	590 mm	340 mm	17,80 kg	277,0 mm
42	1,42 kg	1,70 kg	225 mm	315 mm	115 mm	470 mm	590 mm	340 mm	18,60 kg	283,0 mm
43	1,51 kg	1,81 kg	230 mm	340 mm	120 mm	495 mm	630 mm	355 mm	20,00 kg	290,0 mm
44	1,58 kg	1,88 kg	230 mm	340 mm	120 mm	495 mm	630 mm	355 mm	20,60 kg	297,0 mm
45	1,65 kg	1,96 kg	230 mm	340 mm	120 mm	495 mm	630 mm	355 mm	21,40 kg	306,0 mm
46	1,67 kg	2,00 kg	235 mm	350 mm	125 mm	500 mm	640 mm	370 mm	22,40 kg	312,0 mm
47	1,74 kg	2,08 kg	235 mm	350 mm	125 mm	500 mm	640 mm	370 mm	23,00 kg	320,0 mm
48	1,79 kg	2,16 kg	235 mm	350 mm	125 mm	500 mm	640 mm	370 mm	23,80 kg	326,0 mm

Business parameters

Tarric	64034000
Country	CN
Weight	1,65 kg
Add Unit	NPR

LISABON ankle safety shoes

» Shoes » Safety shoes » Ankle

Add Quantity 1