

CORSICA low cut safety shoes

» Shoes » Safety shoes » Low cut

Technical sheet

CORSICA low cut safety shoes

Product code: 2045-S1PLESD



upper	brushed cow suede leather VELOUR in a thickness of 1,6 - 1,8 mm
lining	laminated breathable fabric MESH
inner insole	HI-POLY - anatomically shaped lightweight polyurethane foam coated with fabric MESH, antistatic
outsole	PU/PU - antistatic, antislip, double density injection
size	36 - 49
standard	EN ISO 20345:2022, EN ISO 61340-5-1:2016
version	S1PL ESD SR - with plastic toe cap and kevlar midsole, antistatic properties ESD, NON METALIC

Properties

PL Midsole penetration protection nonmetallic - PL	Yes
PS Midsole penetration protection nonmetallic - PS	No
SR Antislip prop. on ceramic with glycerol	Yes
WPA Water resistant upper	No
HRO Resist. of the outsole against contact heat	No
WR Water resistant	No

CORSICA low cut safety shoes

» Shoes » Safety shoes » Low cut

WRU Water resistant upper	No
CI Insulation against cold	No
HI Insulation of the outsole against heat	No
FO Resist. of the outsole against fuel oils	No
P Midsole penetration protection	No
E Energy absorption in the heel area	Yes
M Instep protection	No
A Antistatic properties	Yes
AN Ankle protection	No
CR Cut resistant upper	No
SRA Antislip prop. on ceramic tile with SLS	No
SRB Antislip prop. on smooth steel with glycerol	No
SRC Antislip resistance SRA + SRB	No
Free-tex Membrane	No
Michelin Michelin® sole	No
BOA BOA Fit System	No
NON-METALIC Footwear without metal parts	Yes
ESD antistatic properties ESD	Yes
Winter Winter footwear	No
ANTICUT Anti-cut boots	No
Standard	20345:2023
Shoe marking	S1

Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
36	0,93 kg	1,19 kg	200 mm	320 mm	115 mm	420 mm	600 mm	330 mm	12,60 kg	231,0 mm
37	0,93 kg	1,19 kg	200 mm	320 mm	115 mm	420 mm	600 mm	330 mm	12,80 kg	237,7 mm
38	0,97 kg	1,23 kg	200 mm	320 mm	115 mm	420 mm	600 mm	330 mm	13,00 kg	244,3 mm
39	1,02 kg	1,28 kg	200 mm	320 mm	115 mm	420 mm	600 mm	330 mm	13,40 kg	251,0 mm
40	1,05 kg	1,31 kg	200 mm	320 mm	115 mm	420 mm	600 mm	330 mm	13,60 kg	257,7 mm
41	1,08 kg	1,35 kg	200 mm	320 mm	115 mm	420 mm	600 mm	330 mm	13,80 kg	264,3 mm
42	1,13 kg	1,39 kg	200 mm	320 mm	115 mm	420 mm	600 mm	330 mm	14,20 kg	271,0 mm
43	1,17 kg	1,44 kg	200 mm	330 mm	120 mm	430 mm	620 mm	345 mm	15,20 kg	277,7 mm
44	1,20 kg	1,49 kg	200 mm	330 mm	120 mm	430 mm	620 mm	345 mm	15,00 kg	284,3 mm
45	1,27 kg	1,55 kg	200 mm	330 mm	120 mm	430 mm	620 mm	345 mm	16,20 kg	291,0 mm
46	1,29 kg	1,59 kg	210 mm	345 mm	125 mm	440 mm	650 mm	370 mm	16,80 kg	299,7 mm
47	1,35 kg	1,66 kg	210 mm	345 mm	125 mm	440 mm	650 mm	370 mm	17,40 kg	304,4 mm
48	1,43 kg	1,74 kg	210 mm	345 mm	125 mm	440 mm	650 mm	370 mm	18,00 kg	311,0 mm
49	1,44 kg	1,75 kg	210 mm	345 mm	125 mm	440 mm	650 mm	370 mm	18,20 kg	0,0 mm

Business parameters

Tarric	64034000
Country	CN
Weight	1,50 kg

CORSICA low cut safety shoes

» Shoes » Safety shoes » Low cut

Add Unit NPR
Add Quantity 1