

ARKANSAS ankle safety shoes

» Shoes » Safety shoes » Ankle

Technical sheet

ARKANSAS ankle safety shoes

Product code: 6430-S3



upper	licowa skóra bydlęca NUBUK o grubości 1,9 - 2,1 mm
lining	oddychająca, termo-izolująca MEMBRANA FREE-TEX®
inner insole	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
outsole	MICHELIN®-PU/RUBBER - up to 300°C, HRO, SRC, resistant to fuel oils, antislip, antistatic
size	39 - 48
standard	EN ISO 20345:2011
version	S3 HRO SRC CI WR - z podnoskiem kompozytowym, kevlarową wkładką, skóra hydrofobowa, Membrana FREE-TEX®

Properties

PL Midsole penetration protection nonmetallic - PL	No
PS Midsole penetration protection nonmetallic - PS	No
SR Antislip prop. on ceramic with glycerol	No
WPA Water resistant upper	No
HRO Resist. of the outsole against contact heat	Yes

ARKANSAS ankle safety shoes

» Shoes » Safety shoes » Ankle

WR Water resistant	Yes
WRU Water resistant upper	Yes
CI Insulation against cold	Yes
HI Insulation of the outsole against heat	No
FO Resist. of the outsole against fuel oils	Yes
P Midsole penetration protection	Yes
E Energy absorption in the heel area	Yes
M Instep protection	No
A Antistatic properties	No
AN Ankle protection	No
CR Cut resistant upper	No
SRA Antislip prop. on ceramic tile with SLS	Yes
SRB Antislip prop. on smooth steel with glycerol	Yes
SRC Antislip resistance SRA + SRB	Yes
Free-tex Membrane	Yes
Michelin Michelin® sole	Yes
BOA BOA Fit System	No
NON-METALIC Footwear without metal parts	No
ESD antistatic properties ESD	No
Winter Winter footwear	No
ANTICUT Anti-cut boots	No
Standard	20345:2012
Shoe marking	S3

Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
39	1,57 kg	1,86 kg	260 mm	320 mm	115 mm	545 mm	595 mm	350 mm	19,80 kg	260,0 mm
40	1,62 kg	1,92 kg	260 mm	320 mm	115 mm	545 mm	595 mm	350 mm	20,20 kg	266,7 mm
41	1,65 kg	1,95 kg	260 mm	320 mm	115 mm	545 mm	595 mm	350 mm	20,80 kg	273,3 mm
42	1,68 kg	1,97 kg	260 mm	320 mm	115 mm	545 mm	595 mm	350 mm	21,20 kg	280,0 mm
43	1,73 kg	2,18 kg	275 mm	370 mm	140 mm	575 mm	730 mm	400 mm	23,40 kg	286,7 mm
44	1,82 kg	2,28 kg	275 mm	370 mm	140 mm	575 mm	730 mm	400 mm	24,40 kg	293,3 mm
45	1,93 kg	2,38 kg	275 mm	370 mm	140 mm	575 mm	730 mm	400 mm	25,20 kg	300,0 mm
46	1,98 kg	2,44 kg	275 mm	370 mm	140 mm	575 mm	730 mm	400 mm	25,80 kg	306,7 mm
47	2,05 kg	2,50 kg	275 mm	370 mm	140 mm	575 mm	730 mm	400 mm	26,40 kg	313,4 mm
48	2,07 kg	2,53 kg	275 mm	370 mm	140 mm	575 mm	730 mm	400 mm	26,60 kg	320,1 mm

Business parameters

Tarric	64034000
Country	CN
Weight	1,50 kg
Add Unit	NPR
Add Quantity	1