

ANDORRA low cut safety shoes

» Shoes » Safety shoes » Low cut

Technical sheet

ANDORRA low cut safety shoes

Product code: 2315-S3



upper	cowhide leather in a thickness of 2,0 - 2,2 mm
lining	laminated breathable fabric MESH
inner insole	HI-POLY - anatomically shaped lightweight polyurethane foam coated with fabric MESH, antistatic
outsole	PU/RUBBER - up to 300°C, resistant to fuel oils, antistatic, antislip, double density injection
size	37 - 48
standard	EN ISO 20345:2011
version	S3 HRO SRC - with steal toe cap and steal midsole, hydrophobic

Properties

PL Midsole penetration protection nonmetallic - PL	No
PS Midsole penetration protection nonmetallic - PS	No
SR Antislip prop. on ceramic with glycerol	No
WPA Water resistant upper	No
HRO Resist. of the outsole against contact heat	Yes
WR Water resistant	No

ANDORRA low cut safety shoes

» Shoes » Safety shoes » Low cut

WRU Water resistant upper	Yes
CI Insulation against cold	No
HI Insulation of the outsole against heat	No
FO Resist. of the outsole against fuel oils	Yes
P Midsole penetration protection	Yes
E Energy absorption in the heel area	Yes
M Instep protection	No
A Antistatic properties	Yes
AN Ankle protection	No
CR Cut resistant upper	No
SRA Antislip prop. on ceramic tile with SLS	Yes
SRB Antislip prop. on smooth steel with glycerol	Yes
SRC Antislip resistance SRA + SRB	Yes
Free-tex Membrane	No
Michelin Michelin® sole	No
BOA BOA Fit System	No
NON-METALIC Footwear without metal parts	No
ESD antistatic properties ESD	No
Winter Winter footwear	No
ANTICUT Anti-cut boots	No
Standard	20345:2012
Shoe marking	S3

Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
37	1,29 kg	1,59 kg	455 mm	600 mm	355 mm	210 mm	315 mm	120 mm	17,00 kg	237,0 mm
38	1,33 kg	1,62 kg	455 mm	600 mm	355 mm	210 mm	315 mm	120 mm	17,20 kg	244,5 mm
39	1,35 kg	1,66 kg	455 mm	600 mm	355 mm	210 mm	315 mm	120 mm	17,40 kg	252,0 mm
40	1,41 kg	1,70 kg	455 mm	600 mm	355 mm	210 mm	315 mm	120 mm	17,60 kg	259,5 mm
41	1,48 kg	1,76 kg	455 mm	600 mm	355 mm	210 mm	315 mm	120 mm	17,90 kg	267,0 mm
42	1,50 kg	1,77 kg	455 mm	600 mm	355 mm	210 mm	315 mm	120 mm	18,30 kg	274,5 mm
43	1,53 kg	1,81 kg	225 mm	350 mm	125 mm	475 mm	650 mm	375 mm	18,80 kg	282,0 mm
44	1,59 kg	1,89 kg	225 mm	350 mm	125 mm	475 mm	650 mm	375 mm	19,50 kg	289,5 mm
45	1,67 kg	1,98 kg	225 mm	350 mm	125 mm	475 mm	650 mm	375 mm	21,00 kg	297,0 mm
46	1,76 kg	2,09 kg	225 mm	350 mm	125 mm	475 mm	650 mm	375 mm	22,00 kg	304,5 mm
47	1,82 kg	2,15 kg	225 mm	350 mm	125 mm	475 mm	650 mm	375 mm	22,40 kg	312,0 mm
48	1,90 kg	2,24 kg	225 mm	350 mm	125 mm	475 mm	650 mm	375 mm	22,80 kg	319,5 mm

Business parameters

Tarric	64034000
Country	CN
Weight	1,70 kg
Add Unit	NPR

ANDORRA low cut safety shoes

» Shoes » Safety shoes » Low cut

Add Quantity 1