

ALASKA low cut safety shoes

» Shoes » Safety shoes » Low cut

Technical sheet

ALASKA low cut safety shoes

Product code: 8565-S7L



upper	textile in a combination of RIPSTOP
lining	vapor permeable, waterproof GORE-TEX® membrane
inner insole	HI-POLY – anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
outsole	MICHELIN®-EVA/RUBBER – up to 300°C, HRO, SR, resistant to fuel oils, slip resistant, antistatic
size	39 – 48
standard	EN ISO 20345:2022
version	S7L FO HRO SR – with composite toe cap and kevlar midsole, hydrophobic, GORE-TEX® membrane, MICHELIN® Technical Soles

Properties

PL Midsole penetration protection nonmetallic - PL	Yes
PS Midsole penetration protection nonmetallic - PS	No
SR Antislip prop. on ceramic with glycerol	Yes
WPA Water resistant upper	Yes
HRO Resist. of the outsole against contact heat	Yes

ALASKA low cut safety shoes

» Shoes » Safety shoes » Low cut

WR Water resistant	Yes
WRU Water resistant upper	No
CI Insulation against cold	No
HI Insulation of the outsole against heat	No
FO Resist. of the outsole against fuel oils	Yes
P Midsole penetration protection	No
E Energy absorption in the heel area	Yes
M Instep protection	No
A Antistatic properties	Yes
AN Ankle protection	No
CR Cut resistant upper	No
SRA Antislip prop. on ceramic tile with SLS	No
SRB Antislip prop. on smooth steel with glycerol	No
SRC Antislip resistance SRA + SRB	No
Free-tex Membrane	No
Michelin Michelin® sole	Yes
BOA BOA Fit System	No
NON-METALIC Footwear without metal parts	No
ESD antistatic properties ESD	No
Winter Winter footwear	No
ANTICUT Anti-cut boots	No
Standard	20345:2023
Shoe marking	S7

Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
39	1,05 kg	1,29 kg	200 mm	315 mm	120 mm	425 mm	610 mm	345 mm	13,60 kg	254,0 mm
40	1,07 kg	1,31 kg	200 mm	315 mm	120 mm	425 mm	610 mm	345 mm	13,80 kg	261,0 mm
41	1,11 kg	1,34 kg	200 mm	315 mm	120 mm	425 mm	610 mm	345 mm	14,20 kg	268,0 mm
42	1,18 kg	1,42 kg	200 mm	315 mm	120 mm	425 mm	610 mm	345 mm	14,60 kg	275,0 mm
43	1,24 kg	1,52 kg	210 mm	345 mm	125 mm	445 mm	650 mm	370 mm	15,60 kg	282,0 mm
44	1,26 kg	1,53 kg	210 mm	345 mm	125 mm	445 mm	650 mm	370 mm	16,00 kg	289,0 mm
45	1,28 kg	1,55 kg	210 mm	345 mm	125 mm	445 mm	650 mm	370 mm	16,20 kg	296,0 mm
46	1,37 kg	1,63 kg	210 mm	345 mm	125 mm	445 mm	650 mm	370 mm	16,80 kg	303,0 mm
47	1,38 kg	1,65 kg	210 mm	345 mm	125 mm	445 mm	650 mm	370 mm	17,40 kg	310,0 mm
48	0,00 kg	0,00 kg	0 mm	0 mm	0 mm	0 mm	0 mm	0 mm	0,00 kg	0,0 mm

Business parameters

Tarric	64041990
Country	CN
Weight	1,46 kg
Add Unit	NPR
Add Quantity	1