

MALAGA low cut safety shoes

» Shoes » Safety shoes » Low cut

Technical sheet

MALAGA low cut safety shoes

Product code: 3125-S1



upper	knitted, breathable, abrasionresistant textile
lining	laminated breathable fabric MESH
inner insole	HI-POLY – anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
outsole	PU/PU – resistant to fuel oils, antistatic, slip resistant, double density injection
size	36 – 48
standard	EN ISO 20345:2022
version	S1 FO – with steel toe cap

Properties

PL Midsole penetration protection nonmetallic - PL	No
PS Midsole penetration protection nonmetallic - PS	No
SR Antislip prop. on ceramic with glycerol	No
WPA Water resistant upper	No
HRO Resist. of the outsole against contact heat	No
WR Water resistant	No
WRU Water resistant upper	No

MALAGA low cut safety shoes

» Shoes » Safety shoes » Low cut

CI Insulation against cold	No
HI Insulation of the outsole against heat	No
FO Resist. of the outsole against fuel oils	Yes
P Midsole penetration protection	No
E Energy absorption in the heel area	Yes
M Instep protection	No
A Antistatic properties	Yes
AN Ankle protection	No
CR Cut resistant upper	No
SRA Antislip prop. on ceramic tile with SLS	No
SRB Antislip prop. on smooth steel with glycerol	No
SRC Antislip resistance SRA + SRB	No
Free-tex Membrane	No
Michelin Michelin® sole	No
BOA BOA Fit System	No
NON-METALIC Footwear without metal parts	No
ESD antistatic properties ESD	No
Winter Winter footwear	No
ANTICUT Anti-cut boots	No
Standard	20345:2023
Shoe marking	S1

Logistics parameters

Velikost	Net weight	Gross weight	Sales box - widht	Sales box - length	Sales box - height	Group packaging - widht	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
36	0,00 kg	0,00 kg	0 mm	0 mm	0 mm	0 mm	0 mm	0 mm	0,00 kg	0,0 mm
37	0,00 kg	0,00 kg	0 mm	0 mm	0 mm	0 mm	0 mm	0 mm	0,00 kg	0,0 mm
38	0,00 kg	0,00 kg	0 mm	0 mm	0 mm	0 mm	0 mm	0 mm	0,00 kg	0,0 mm
39	0,00 kg	0,00 kg	0 mm	0 mm	0 mm	0 mm	0 mm	0 mm	0,00 kg	0,0 mm
40	0,00 kg	0,00 kg	0 mm	0 mm	0 mm	0 mm	0 mm	0 mm	0,00 kg	0,0 mm
41	0,00 kg	0,00 kg	0 mm	0 mm	0 mm	0 mm	0 mm	0 mm	0,00 kg	0,0 mm
42	0,00 kg	0,00 kg	0 mm	0 mm	0 mm	0 mm	0 mm	0 mm	0,00 kg	0,0 mm
43	0,00 kg	0,00 kg	0 mm	0 mm	0 mm	0 mm	0 mm	0 mm	0,00 kg	0,0 mm
44	0,00 kg	0,00 kg	0 mm	0 mm	0 mm	0 mm	0 mm	0 mm	0,00 kg	0,0 mm
45	0,00 kg	0,00 kg	0 mm	0 mm	0 mm	0 mm	0 mm	0 mm	0,00 kg	0,0 mm
46	0,00 kg	0,00 kg	0 mm	0 mm	0 mm	0 mm	0 mm	0 mm	0,00 kg	0,0 mm
47	0,00 kg	0,00 kg	0 mm	0 mm	0 mm	0 mm	0 mm	0 mm	0,00 kg	0,0 mm
48	0,00 kg	0,00 kg	0 mm	0 mm	0 mm	0 mm	0 mm	0 mm	0,00 kg	0,0 mm

Business parameters

Tarric	64034000
Country	CN
Weight	1,27 kg
Add Unit	NPR

MALAGA low cut safety shoes

» Shoes » Safety shoes » Low cut

Add Quantity 1