

UMAG ankle occupational shoes

» Shoes » Occupational shoes » Ankle

Technical sheet

UMAG ankle occupational shoes

Product code: 3180-02



upper	corrected cow leather with pattern in a thickness of 1,6 – 1,8 mm
lining	MESH fabric with absorbency
inner insole	HI-POLY – anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
outsole	PU/PU – resistant to fuel oils, antistatic, slip resistant, double density injection
size	36 – 48
standard	EN ISO 20347:2022
version	O2 FO SR – without steel toe cap, hydrophobic

Properties

PL Midsole penetration protection nonmetallic - PL	No
PS Midsole penetration protection nonmetallic - PS	No
SR Antislip prop. on ceramic with glycerol	Yes
WPA Water resistant upper	Yes
HRO Resist. of the outsole against contact heat	No
WR Water resistant	No
WRU Water resistant upper	No

UMAG ankle occupational shoes

» Shoes » Occupational shoes » Ankle

CI Insulation against cold	No
HI Insulation of the outsole against heat	No
FO Resist. of the outsole against fuel oils	Yes
P Midsole penetration protection	No
E Energy absorption in the heel area	Yes
M Instep protection	No
A Antistatic properties	Yes
AN Ankle protection	No
CR Cut resistant upper	No
SRA Antislip prop. on ceramic tile with SLS	No
SRB Antislip prop. on smooth steel with glycerol	No
SRC Antislip resistance SRA + SRB	No
Free-tex Membrane	No
Michelin Michelin® sole	No
BOA BOA Fit System	No
NON-METALIC Footwear without metal parts	No
ESD antistatic properties ESD	No
Winter Winter footwear	No
ANTICUT Anti-cut boots	No
Standard	20347:2023
Shoe marking	O2

Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
35	0,66 kg	0,89 kg	200 mm	315 mm	115 mm	410 mm	590 mm	330 mm	9,60 kg	0,0 mm
36	0,67 kg	0,90 kg	200 mm	315 mm	115 mm	410 mm	590 mm	330 mm	9,80 kg	0,0 mm
37	0,68 kg	0,92 kg	200 mm	315 mm	115 mm	410 mm	590 mm	330 mm	10,00 kg	0,0 mm
38	0,72 kg	0,96 kg	200 mm	315 mm	115 mm	410 mm	590 mm	330 mm	10,20 kg	0,0 mm
39	0,75 kg	0,98 kg	200 mm	315 mm	115 mm	410 mm	590 mm	330 mm	10,40 kg	0,0 mm
40	0,78 kg	1,01 kg	200 mm	315 mm	115 mm	410 mm	590 mm	330 mm	10,60 kg	0,0 mm
41	0,80 kg	1,03 kg	200 mm	315 mm	115 mm	410 mm	590 mm	330 mm	11,00 kg	0,0 mm
42	0,82 kg	1,05 kg	200 mm	315 mm	115 mm	410 mm	590 mm	330 mm	11,20 kg	0,0 mm
43	0,84 kg	1,07 kg	205 mm	325 mm	115 mm	420 mm	600 mm	340 mm	11,60 kg	0,0 mm
44	0,86 kg	1,09 kg	205 mm	325 mm	115 mm	420 mm	600 mm	340 mm	11,80 kg	0,0 mm
45	0,89 kg	1,13 kg	210 mm	350 mm	120 mm	435 mm	620 mm	365 mm	12,20 kg	0,0 mm
46	0,91 kg	1,16 kg	210 mm	350 mm	120 mm	435 mm	620 mm	365 mm	12,40 kg	0,0 mm
47	0,94 kg	1,19 kg	210 mm	350 mm	120 mm	435 mm	620 mm	365 mm	12,90 kg	0,0 mm
48	0,97 kg	1,21 kg	210 mm	350 mm	120 mm	435 mm	620 mm	365 mm	13,20 kg	0,0 mm
49	1,03 kg	1,27 kg	210 mm	350 mm	120 mm	435 mm	620 mm	365 mm	13,90 kg	0,0 mm
50	1,07 kg	1,31 kg	215 mm	355 mm	125 mm	445 mm	645 mm	390 mm	14,40 kg	0,0 mm

Business parameters

Tarric	64039113
Country	CN

UMAG ankle occupational shoes

» Shoes » Occupational shoes » Ankle

Weight	1,80 kg
Add Unit	NPR
Add Quantity	1