

PALERMO low cut safety shoes BOA

» Shoes » Safety shoes » Low cut

Technical sheet

PALERMO low cut safety shoes BOA

Product code: 2085-S1PLESD



upper	abrasion resistant textiles
lining	laminated breathable fabric MESH
inner insole	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
outsole	PU/PU - oil resistant, antistatic, antislip, double density injection
size	36 - 49
standard	EN ISO 20345:2022, EN ISO 61340-5-1:2016
version	S1 PL FO SR ESD - with composite toe cap and kevlar midsole - antistatic properties ESD

Properties

PL Midsole penetration protection nonmetallic - PL	Yes
PS Midsole penetration protection nonmetallic - PS	No
SR Antislip prop. on ceramic with glycerol	Yes
WPA Water resistant upper	No
HRO Resist. of the outsole against contact heat	No
WR Water resistant	No

PALERMO low cut safety shoes BOA

» Shoes » Safety shoes » Low cut

WRU Water resistant upper	No
CI Insulation against cold	No
HI Insulation of the outsole against heat	No
FO Resist. of the outsole against fuel oils	Yes
P Midsole penetration protection	No
E Energy absorption in the heel area	Yes
M Instep protection	No
A Antistatic properties	Yes
AN Ankle protection	No
CR Cut resistant upper	No
SRA Antislip prop. on ceramic tile with SLS	No
SRB Antislip prop. on smooth steel with glycerol	No
SRC Antislip resistance SRA + SRB	No
Free-tex Membrane	No
Michelin Michelin® sole	No
BOA BOA Fit System	Yes
NON-METALIC Footwear without metal parts	No
ESD antistatic properties ESD	Yes
Winter Winter footwear	No
ANTICUT Anti-cut boots	No
Standard	20345:2023
Shoe marking	S1

Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
36	0,83 kg	1,07 kg	200 mm	315 mm	120 mm	415 mm	615 mm	330 mm	11,60 kg	235,0 mm
37	0,86 kg	1,10 kg	200 mm	315 mm	120 mm	415 mm	615 mm	330 mm	11,80 kg	242,0 mm
38	0,91 kg	1,13 kg	200 mm	315 mm	120 mm	415 mm	615 mm	330 mm	12,20 kg	249,0 mm
39	0,94 kg	1,18 kg	200 mm	315 mm	120 mm	415 mm	615 mm	330 mm	12,60 kg	256,0 mm
40	1,00 kg	1,24 kg	200 mm	315 mm	120 mm	415 mm	615 mm	330 mm	13,00 kg	263,0 mm
41	1,04 kg	1,29 kg	200 mm	315 mm	120 mm	415 mm	615 mm	330 mm	13,40 kg	270,0 mm
42	1,08 kg	1,32 kg	200 mm	315 mm	120 mm	415 mm	615 mm	330 mm	14,00 kg	277,0 mm
43	1,10 kg	1,33 kg	200 mm	315 mm	120 mm	415 mm	615 mm	330 mm	14,20 kg	284,0 mm
44	1,13 kg	1,39 kg	210 mm	345 mm	125 mm	435 mm	640 mm	360 mm	15,00 kg	291,0 mm
45	1,14 kg	1,40 kg	210 mm	345 mm	125 mm	435 mm	640 mm	360 mm	15,40 kg	298,0 mm
46	1,25 kg	1,51 kg	210 mm	345 mm	125 mm	435 mm	640 mm	360 mm	15,80 kg	305,0 mm
47	1,27 kg	1,53 kg	210 mm	345 mm	125 mm	435 mm	640 mm	360 mm	16,20 kg	312,0 mm
48	1,28 kg	1,54 kg	210 mm	345 mm	125 mm	435 mm	640 mm	360 mm	16,40 kg	319,0 mm
49	1,30 kg	1,56 kg	210 mm	345 mm	125 mm	435 mm	640 mm	360 mm	16,70 kg	326,0 mm

Business parameters

Tarric	64041990
Country	CN
Weight	1,45 kg

PALERMO low cut safety shoes BOA

» Shoes » Safety shoes » Low cut

Add Unit	NPR
Add Quantity	1