

# MICHIGAN safety sandal

» Shoes » Safety shoes » Sandals

## Technical sheet

### MICHIGAN safety sandal



Product code: 2145-S1PESD



|                     |                                                                                                 |
|---------------------|-------------------------------------------------------------------------------------------------|
| <b>upper</b>        | brushed cow suede leather VELOUR in a thickness of 1,6 - 1,8 mm                                 |
| <b>lining</b>       | laminated breathable fabric MESH                                                                |
| <b>inner insole</b> | HI-POLY - anatomically shaped lightweight polyurethane foam coated with fabric MESH, antistatic |
| <b>outsole</b>      | PU/PU - resistant to fuel oils, antistatic, antislip, double density injection                  |
| <b>size</b>         | 36 - 48                                                                                         |
| <b>standard</b>     | EN ISO 20345:2011, EN ISO 61340-5-1:2016                                                        |
| <b>version</b>      | S1P ESD SRA - with plastic toe cap and kevlar midsole, antistatic properties ESD, NON METALIC   |

## Properties

|                                                           |    |
|-----------------------------------------------------------|----|
| <b>PL</b> Midsole penetration protection nonmetallic - PL | No |
| <b>PS</b> Midsole penetration protection nonmetallic - PS | No |
| <b>SR</b> Antislip prop. on ceramic with glycerol         | No |
| <b>WPA</b> Water resistant upper                          | No |
| <b>HRO</b> Resist. of the outsole against contact heat    | No |
| <b>WR</b> Water resistant                                 | No |

# MICHIGAN safety sandal

» Shoes » Safety shoes » Sandals

|                                                         |            |
|---------------------------------------------------------|------------|
| <b>WRU</b> Water resistant upper                        | No         |
| <b>CI</b> Insulation against cold                       | No         |
| <b>HI</b> Insulation of the outsole against heat        | No         |
| <b>FO</b> Resist. of the outsole against fuel oils      | Yes        |
| <b>P</b> Midsole penetration protection                 | Yes        |
| <b>E</b> Energy absorption in the heel area             | Yes        |
| <b>M</b> Instep protection                              | No         |
| <b>A</b> Antistatic properties                          | Yes        |
| <b>AN</b> Ankle protection                              | No         |
| <b>CR</b> Cut resistant upper                           | No         |
| <b>SRA</b> Antislip prop. on ceramic tile with SLS      | Yes        |
| <b>SRB</b> Antislip prop. on smooth steel with glycerol | No         |
| <b>SRC</b> Antislip resistance SRA + SRB                | No         |
| <b>Free-tex</b> Membrane                                | No         |
| <b>Michelin</b> Michelin® sole                          | No         |
| <b>BOA</b> BOA Fit System                               | No         |
| <b>NON-METALIC</b> Footwear without metal parts         | Yes        |
| <b>ESD</b> antistatic properties ESD                    | Yes        |
| <b>Winter</b> Winter footwear                           | No         |
| <b>ANTICUT</b> Anti-cut boots                           | No         |
| <b>Standard</b>                                         | 20345:2012 |
| <b>Shoe marking</b>                                     | S1         |

## Logistics parameters

| Velikost | Net weight | Gross weight | Sales box - width | Sales box - length | Sales box - height | Group packaging - width | Group packaging - length | Group packaging - height | Group packaging - weight | Vnitřní délka obuvi |
|----------|------------|--------------|-------------------|--------------------|--------------------|-------------------------|--------------------------|--------------------------|--------------------------|---------------------|
| 36       | 0,73 kg    | 0,97 kg      | 200 mm            | 315 mm             | 115 mm             | 420 mm                  | 600 mm                   | 340 mm                   | 10,60 kg                 | 231,0 mm            |
| 37       | 0,78 kg    | 1,02 kg      | 200 mm            | 315 mm             | 115 mm             | 420 mm                  | 600 mm                   | 340 mm                   | 11,00 kg                 | 237,7 mm            |
| 38       | 0,80 kg    | 1,04 kg      | 200 mm            | 315 mm             | 115 mm             | 420 mm                  | 600 mm                   | 340 mm                   | 11,20 kg                 | 244,3 mm            |
| 39       | 0,86 kg    | 1,09 kg      | 200 mm            | 315 mm             | 115 mm             | 420 mm                  | 600 mm                   | 340 mm                   | 11,40 kg                 | 251,0 mm            |
| 40       | 0,84 kg    | 1,08 kg      | 200 mm            | 315 mm             | 115 mm             | 420 mm                  | 600 mm                   | 340 mm                   | 11,60 kg                 | 257,7 mm            |
| 41       | 0,87 kg    | 1,11 kg      | 200 mm            | 315 mm             | 115 mm             | 420 mm                  | 600 mm                   | 340 mm                   | 11,80 kg                 | 264,3 mm            |
| 42       | 0,92 kg    | 1,15 kg      | 200 mm            | 315 mm             | 115 mm             | 420 mm                  | 600 mm                   | 340 mm                   | 12,40 kg                 | 271,0 mm            |
| 43       | 0,94 kg    | 1,20 kg      | 205 mm            | 330 mm             | 125 mm             | 430 mm                  | 620 mm                   | 360 mm                   | 12,80 kg                 | 277,7 mm            |
| 44       | 0,96 kg    | 1,22 kg      | 205 mm            | 330 mm             | 125 mm             | 430 mm                  | 620 mm                   | 360 mm                   | 13,00 kg                 | 284,3 mm            |
| 45       | 1,03 kg    | 1,30 kg      | 205 mm            | 330 mm             | 125 mm             | 430 mm                  | 620 mm                   | 360 mm                   | 13,60 kg                 | 291,0 mm            |
| 46       | 1,05 kg    | 1,34 kg      | 210 mm            | 350 mm             | 130 mm             | 440 mm                  | 655 mm                   | 375 mm                   | 14,20 kg                 | 299,7 mm            |
| 47       | 1,07 kg    | 1,34 kg      | 210 mm            | 350 mm             | 130 mm             | 440 mm                  | 655 mm                   | 375 mm                   | 14,30 kg                 | 304,4 mm            |
| 48       | 1,08 kg    | 1,35 kg      | 210 mm            | 350 mm             | 130 mm             | 440 mm                  | 655 mm                   | 375 mm                   | 14,40 kg                 | 311,0 mm            |

## Business parameters

|                |          |
|----------------|----------|
| <b>Tarric</b>  | 64034000 |
| <b>Country</b> | CN       |
| <b>Weight</b>  | 1,50 kg  |

# MICHIGAN safety sandal

» Shoes » Safety shoes » Sandals

|                     |     |
|---------------------|-----|
| <b>Add Unit</b>     | NPR |
| <b>Add Quantity</b> | 1   |