

MILWAUKEE low cut safety shoes

» Shoes » Safety shoes » Low cut

Technical sheet

MILWAUKEE low cut safety shoes

Product code: 8185-S3ESD



upper	polyamide abrasion resistant fabric PUTEK
lining	laminated breathable fabric MESH
inner insole	HI-POLY – anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
outsole	MICHELIN®-PU/RUBBER – resistant to fuel oils, antistatic, antislip
size	36 – 47
standard	EN ISO 20345:2011, EN ISO 61340-5-1:2016
version	S3 ESD SRC – with composite toe cap and kevlar midsole – antistatic properties ESD, NON METALLIC

Properties

PL Midsole penetration protection nonmetallic - PL	No
PS Midsole penetration protection nonmetallic - PS	No
SR Antislip prop. on ceramic with glycerol	No
WPA Water resistant upper	No
HRO Resist. of the outsole against contact heat	No
WR Water resistant	No

MILWAUKEE low cut safety shoes

» Shoes » Safety shoes » Low cut

WRU Water resistant upper	Yes
CI Insulation against cold	No
HI Insulation of the outsole against heat	No
FO Resist. of the outsole against fuel oils	Yes
P Midsole penetration protection	Yes
E Energy absorption in the heel area	Yes
M Instep protection	No
A Antistatic properties	Yes
AN Ankle protection	No
CR Cut resistant upper	No
SRA Antislip prop. on ceramic tile with SLS	Yes
SRB Antislip prop. on smooth steel with glycerol	Yes
SRC Antislip resistance SRA + SRB	Yes
Free-tex Membrane	No
Michelin Michelin® sole	Yes
BOA BOA Fit System	No
NON-METALIC Footwear without metal parts	No
ESD antistatic properties ESD	No
Winter Winter footwear	No
ANTICUT Anti-cut boots	No
Standard	20345:2012
Shoe marking	S3

Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
36	0,92 kg	1,18 kg	200 mm	315 mm	120 mm	425 mm	620 mm	330 mm	12,20 kg	233,0 mm
37	0,93 kg	1,19 kg	200 mm	315 mm	120 mm	425 mm	620 mm	330 mm	12,40 kg	240,0 mm
38	0,97 kg	1,24 kg	200 mm	315 mm	120 mm	425 mm	620 mm	330 mm	12,80 kg	247,0 mm
39	1,01 kg	1,27 kg	200 mm	315 mm	120 mm	425 mm	620 mm	330 mm	13,40 kg	254,0 mm
40	1,04 kg	1,31 kg	200 mm	315 mm	120 mm	425 mm	620 mm	330 mm	13,80 kg	261,0 mm
41	0,08 kg	1,35 kg	200 mm	315 mm	120 mm	425 mm	620 mm	330 mm	14,20 kg	268,0 mm
42	1,13 kg	1,40 kg	200 mm	315 mm	120 mm	425 mm	620 mm	330 mm	14,60 kg	275,0 mm
43	1,19 kg	1,48 kg	210 mm	345 mm	125 mm	445 mm	650 mm	360 mm	15,60 kg	282,0 mm
44	1,24 kg	1,54 kg	210 mm	345 mm	125 mm	445 mm	650 mm	360 mm	16,20 kg	289,0 mm
45	1,28 kg	1,56 kg	210 mm	345 mm	125 mm	445 mm	650 mm	360 mm	16,40 kg	296,0 mm
46	1,33 kg	1,63 kg	210 mm	345 mm	125 mm	445 mm	650 mm	360 mm	17,00 kg	303,0 mm
47	1,38 kg	1,68 kg	210 mm	345 mm	125 mm	445 mm	650 mm	360 mm	17,40 kg	310,0 mm

Business parameters

Tarric	64041990
Country	CN
Weight	1,50 kg
Add Unit	NPR

MILWAUKEE low cut safety shoes

» Shoes » Safety shoes » Low cut

Add Quantity 1