

# EDMONTON safety sandal

» Shoes » Safety shoes » Sandals

## Technical sheet

### EDMONTON safety sandal

Product code: 2275-S1PLESD



|                     |                                                                                                   |
|---------------------|---------------------------------------------------------------------------------------------------|
| <b>upper</b>        | brushed, breathable poromeric microfiber material                                                 |
| <b>lining</b>       | laminated breathable fabric MESH                                                                  |
| <b>inner insole</b> | HI-POLY - anatomically shaped lightweight polyurethane foam coated with fabric MESH, antistatic   |
| <b>outsole</b>      | PU/PU - resistant to fuel oils, antistatic, antislip, double density injection                    |
| <b>size</b>         | 36 - 49                                                                                           |
| <b>standard</b>     | EN ISO 20345:2022, EN ISO 61340-5-1:2016                                                          |
| <b>version</b>      | S1 PL FO SR ESD - with plastic toe cap and kevlar midsole, antistatic properties ESD, NON METALIC |

## Properties

|                                                           |     |
|-----------------------------------------------------------|-----|
| <b>PL</b> Midsole penetration protection nonmetallic - PL | Yes |
| <b>PS</b> Midsole penetration protection nonmetallic - PS | No  |
| <b>SR</b> Antislip prop. on ceramic with glycerol         | Yes |
| <b>WPA</b> Water resistant upper                          | No  |
| <b>HRO</b> Resist. of the outsole against contact heat    | No  |
| <b>WR</b> Water resistant                                 | No  |

# EDMONTON safety sandal

» Shoes » Safety shoes » Sandals

|                                                         |            |
|---------------------------------------------------------|------------|
| <b>WRU</b> Water resistant upper                        | No         |
| <b>CI</b> Insulation against cold                       | No         |
| <b>HI</b> Insulation of the outsole against heat        | No         |
| <b>FO</b> Resist. of the outsole against fuel oils      | Yes        |
| <b>P</b> Midsole penetration protection                 | No         |
| <b>E</b> Energy absorption in the heel area             | Yes        |
| <b>M</b> Instep protection                              | No         |
| <b>A</b> Antistatic properties                          | Yes        |
| <b>AN</b> Ankle protection                              | No         |
| <b>CR</b> Cut resistant upper                           | No         |
| <b>SRA</b> Antislip prop. on ceramic tile with SLS      | No         |
| <b>SRB</b> Antislip prop. on smooth steel with glycerol | No         |
| <b>SRC</b> Antislip resistance SRA + SRB                | No         |
| <b>Free-tex</b> Membrane                                | No         |
| <b>Michelin</b> Michelin® sole                          | No         |
| <b>BOA</b> BOA Fit System                               | No         |
| <b>NON-METALIC</b> Footwear without metal parts         | Yes        |
| <b>ESD</b> antistatic properties ESD                    | Yes        |
| <b>Winter</b> Winter footwear                           | No         |
| <b>ANTICUT</b> Anti-cut boots                           | No         |
| <b>Standard</b>                                         | 20345:2023 |
| <b>Shoe marking</b>                                     | S1         |

## Logistics parameters

| Velikost | Net weight | Gross weight | Sales box - width | Sales box - length | Sales box - height | Group packaging - width | Group packaging - length | Group packaging - height | Group packaging - weight | Vnitřní délka obuvi |
|----------|------------|--------------|-------------------|--------------------|--------------------|-------------------------|--------------------------|--------------------------|--------------------------|---------------------|
| 36       | 0,80 kg    | 1,03 kg      | 200 mm            | 315 mm             | 120 mm             | 420 mm                  | 610 mm                   | 340 mm                   | 11,40 kg                 | 235,0 mm            |
| 37       | 0,83 kg    | 1,06 kg      | 200 mm            | 315 mm             | 120 mm             | 420 mm                  | 610 mm                   | 340 mm                   | 11,60 kg                 | 242,0 mm            |
| 38       | 0,88 kg    | 1,10 kg      | 200 mm            | 315 mm             | 120 mm             | 420 mm                  | 610 mm                   | 340 mm                   | 11,80 kg                 | 249,0 mm            |
| 39       | 0,93 kg    | 1,16 kg      | 200 mm            | 315 mm             | 120 mm             | 420 mm                  | 610 mm                   | 340 mm                   | 12,40 kg                 | 256,0 mm            |
| 40       | 0,94 kg    | 1,17 kg      | 200 mm            | 315 mm             | 120 mm             | 420 mm                  | 610 mm                   | 340 mm                   | 12,60 kg                 | 263,0 mm            |
| 41       | 1,01 kg    | 1,24 kg      | 200 mm            | 315 mm             | 120 mm             | 420 mm                  | 610 mm                   | 340 mm                   | 13,00 kg                 | 270,0 mm            |
| 42       | 1,08 kg    | 1,31 kg      | 200 mm            | 315 mm             | 120 mm             | 420 mm                  | 610 mm                   | 340 mm                   | 14,00 kg                 | 277,0 mm            |
| 43       | 1,08 kg    | 1,33 kg      | 210 mm            | 345 mm             | 125 mm             | 440 mm                  | 645 mm                   | 370 mm                   | 14,20 kg                 | 284,0 mm            |
| 44       | 1,10 kg    | 1,37 kg      | 210 mm            | 345 mm             | 125 mm             | 440 mm                  | 645 mm                   | 370 mm                   | 14,60 kg                 | 291,0 mm            |
| 45       | 1,11 kg    | 1,38 kg      | 210 mm            | 345 mm             | 125 mm             | 440 mm                  | 645 mm                   | 365 mm                   | 14,80 kg                 | 298,0 mm            |
| 46       | 1,14 kg    | 1,40 kg      | 210 mm            | 345 mm             | 130 mm             | 440 mm                  | 645 mm                   | 365 mm                   | 15,00 kg                 | 305,0 mm            |
| 47       | 1,19 kg    | 1,45 kg      | 210 mm            | 345 mm             | 130 mm             | 440 mm                  | 645 mm                   | 365 mm                   | 15,40 kg                 | 312,0 mm            |
| 48       | 1,24 kg    | 1,49 kg      | 210 mm            | 345 mm             | 130 mm             | 440 mm                  | 645 mm                   | 365 mm                   | 15,80 kg                 | 319,0 mm            |
| 49       | 1,30 kg    | 1,56 kg      | 210 mm            | 360 mm             | 130 mm             | 445 mm                  | 660 mm                   | 375 mm                   | 16,60 kg                 | 326,0 mm            |

## Business parameters

|                |          |
|----------------|----------|
| <b>Tarric</b>  | 64041990 |
| <b>Country</b> | CN       |
| <b>Weight</b>  | 1,24 kg  |

# EDMONTON safety sandal

» Shoes » Safety shoes » Sandals

**Add Unit**        NPR  
**Add Quantity**    1