

LOUISIANA low cut safety shoes BOA

» Shoes » Safety shoes » Low cut

Technical sheet

LOUISIANA low cut safety shoes BOA

Product code: 6335-S1P



upper	breathable abrasion resistant textile with TPU print
lining	laminated breathable fabric MESH
inner insole	HI-POLY - anatomically shaped lightweight polyuretane foam coated with fabric MESH, antistatic
outsole	EVA/RUBBER - resistant to fuel oils, antistatic, antislip, glued construction
size	39 - 47
standard	EN ISO 20345:2011
version	S1P SRC - with composite toe cap and kevlar midsole

Properties

PL Midsole penetration protection nonmetallic - PL	No
PS Midsole penetration protection nonmetallic - PS	No
SR Antislip prop. on ceramic with glycerol	No
WPA Water resistant upper	No
HRO Resist. of the outsole against contact heat	No
WR Water resistant	No
WRU Water resistant upper	No

LOUISIANA low cut safety shoes BOA

» Shoes » Safety shoes » Low cut

CI Insulation against cold	No
HI Insulation of the outsole against heat	No
FO Resist. of the outsole against fuel oils	Yes
P Midsole penetration protection	Yes
E Energy absorption in the heel area	Yes
M Instep protection	No
A Antistatic properties	Yes
AN Ankle protection	No
CR Cut resistant upper	No
SRA Antislip prop. on ceramic tile with SLS	Yes
SRB Antislip prop. on smooth steel with glycerol	Yes
SRC Antislip resistance SRA + SRB	Yes
Free-tex Membrane	No
Michelin Michelin® sole	No
BOA BOA Fit System	Yes
NON-METALIC Footwear without metal parts	No
ESD antistatic properties ESD	No
Winter Winter footwear	No
ANTICUT Anti-cut boots	No
Standard	20345:2012
Shoe marking	S1

Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
39	1,04 kg	1,32 kg	210 mm	320 mm	115 mm	440 mm	600 mm	350 mm	14,00 kg	257,0 mm
40	1,11 kg	1,39 kg	210 mm	320 mm	115 mm	440 mm	600 mm	350 mm	14,60 kg	263,7 mm
41	1,12 kg	1,39 kg	210 mm	320 mm	115 mm	440 mm	600 mm	350 mm	14,80 kg	270,3 mm
42	1,18 kg	1,46 kg	210 mm	320 mm	115 mm	440 mm	600 mm	350 mm	15,60 kg	277,0 mm
43	1,26 kg	1,58 kg	230 mm	350 mm	125 mm	465 mm	640 mm	375 mm	16,60 kg	283,7 mm
44	1,28 kg	1,60 kg	230 mm	350 mm	125 mm	465 mm	640 mm	375 mm	16,80 kg	290,3 mm
45	1,30 kg	1,62 kg	230 mm	350 mm	125 mm	465 mm	640 mm	375 mm	17,20 kg	297,0 mm
46	1,38 kg	1,69 kg	230 mm	350 mm	125 mm	465 mm	640 mm	375 mm	17,80 kg	303,7 mm
47	1,40 kg	1,72 kg	230 mm	350 mm	125 mm	465 mm	640 mm	375 mm	18,20 kg	310,3 mm

Business parameters

Tarric	64041990
Country	CN
Weight	1,50 kg
Add Unit	NPR
Add Quantity	1