





DANCE S1P

KU055HF

CE UNI EN ISO 20345:2012 S1P SRC ESD CLASS 3

Low shoe, suede back leather thickness 1,8 - 2,0 mm External 3D fabric, perspiring and abrasion resistant. Soft, lined and padded tongue.

COMPLETELY METAL FREE SHOE

TOECAP 200J polymeric composite non-thermic according to EN

MIDSOLE flexible antiperforation composite fabric according to EN 12568

SOLE KUBE bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, antishock and anti-slipping SRC

INSOLE 5000, three-materials extracomfort: perspiring, removable, anatomic, absorbing, ESD and anti-bacterial The shoe satisfies the requirement according to the norm IEC 61340-4-3:2001 for the electrical resistance **ESD class 3 (electric** dissipative footwear)

Size 35-42 Shoe weight Sz 42 gr. 485



CERTIFICATIONS









TECHNOLOGIES AND MATERIALS

















SECTORS



COMPONENTS AND AUTOMOTIVE



WOOD METAL CARPENTRY



LOGISTICS AND LIGHT INDUSTRY



ESD AREAS

SOLE



In order to avoid the high number of accidents caused by slipping danger, Giasco realized an excellent anti-slipping product. This sole is called Kube, a young and sporty styled shoe equipped with a special gripping compound and specific cubic dowels with inverted profile in the outsole. With thanks to these special characteristics Kube obtained the maximum certification against slipping: jobs on inclined roofs (UNI 11583:2015).

PLUS



AIRNET®

 $\label{eq:linear_problem} \mbox{Airnet} \mbox{\ensuremath{\$}} \mbox{ is a certified technology that guarantees the maximum perspiration of } \mbox{\ensuremath{\bullet}} \mbox{\$ the foot by wearing a strong and abrasion resistant safety shoe. Thanks to its construction air tunnel, facilitates the air passage and the material, 100%polyester, guarantees a perfect resistance to abrasion, to traction, to tearing and to washing.

ANTISLIPPING TEST RESULTS

