

MIAMI low cut safety shoes

» Shoes » Safety shoes » Low cut

Technical sheet

MIAMI low cut safety shoes

Product code: 5125-S3



upper	cowhide leather NUBUCK in a thickness of 1,8 – 2,0 mm
lining	laminated breathable fabric MESH
inner insole	anatomically shaped from material EVA with a high absorbency, antistatic
outsole	PU/TPU – transparent – resistant to fuel oils, antistatic, antislip, double density injection
size	36 – 48
standard	EN ISO 20345:2011
version	S3 SRC – with composite toe cap and kevlar midsole, hydrophobic, NON METALLIC

Properties

PL Midsole penetration protection nonmetallic - PL	No
PS Midsole penetration protection nonmetallic - PS	No
SR Antislip prop. on ceramic with glycerol	No
WPA Water resistant upper	No
HRO Resist. of the outsole against contact heat	No
WR Water resistant	No
WRU Water resistant upper	Yes

MIAMI low cut safety shoes

» Shoes » Safety shoes » Low cut

CI Insulation against cold	No
HI Insulation of the outsole against heat	No
FO Resist. of the outsole against fuel oils	Yes
P Midsole penetration protection	Yes
E Energy absorption in the heel area	Yes
M Instep protection	No
A Antistatic properties	Yes
AN Ankle protection	No
CR Cut resistant upper	No
SRA Antislip prop. on ceramic tile with SLS	Yes
SRB Antislip prop. on smooth steel with glycerol	Yes
SRC Antislip resistance SRA + SRB	Yes
Free-tex Membrane	No
Michelin Michelin® sole	No
BOA BOA Fit System	No
NON-METALIC Footwear without metal parts	Yes
ESD antistatic properties ESD	No
Winter Winter footwear	No
ANTICUT Anti-cut boots	No
Standard	20345:2012
Shoe marking	S3

Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
36	1,06 kg	1,31 kg	200 mm	315 mm	115 mm	435 mm	600 mm	340 mm	14,40 kg	233,0 mm
37	1,10 kg	1,36 kg	200 mm	315 mm	115 mm	435 mm	600 mm	340 mm	14,60 kg	244,0 mm
38	1,11 kg	1,37 kg	200 mm	315 mm	115 mm	435 mm	600 mm	340 mm	15,20 kg	250,0 mm
39	1,13 kg	1,40 kg	200 mm	315 mm	115 mm	435 mm	600 mm	340 mm	15,60 kg	257,0 mm
40	1,24 kg	1,47 kg	200 mm	315 mm	115 mm	435 mm	600 mm	340 mm	16,00 kg	263,0 mm
41	1,26 kg	1,50 kg	200 mm	315 mm	115 mm	435 mm	600 mm	340 mm	16,40 kg	272,0 mm
42	1,29 kg	1,52 kg	200 mm	315 mm	115 mm	435 mm	600 mm	340 mm	16,60 kg	279,0 mm
43	1,34 kg	1,62 kg	205 mm	330 mm	120 mm	440 mm	635 mm	355 mm	17,40 kg	285,0 mm
44	1,39 kg	1,66 kg	205 mm	330 mm	120 mm	440 mm	635 mm	355 mm	18,20 kg	291,0 mm
45	1,53 kg	1,79 kg	205 mm	330 mm	120 mm	440 mm	635 mm	355 mm	19,20 kg	300,0 mm
46	1,60 kg	1,88 kg	210 mm	350 mm	125 mm	440 mm	650 mm	370 mm	20,00 kg	308,0 mm
47	1,61 kg	1,92 kg	210 mm	350 mm	125 mm	440 mm	650 mm	370 mm	20,80 kg	312,0 mm
48	1,67 kg	1,97 kg	210 mm	350 mm	125 mm	440 mm	650 mm	370 mm	21,20 kg	319,0 mm

Business parameters

Tarric	64034000
Country	CN
Weight	1,42 kg
Add Unit	NPR

MIAMI low cut safety shoes

» Shoes » Safety shoes » Low cut

Add Quantity 1