

ASTANA low cut safety shoes

» Shoes » Safety shoes » Low cut

Technical sheet

ASTANA low cut safety shoes

Product code: 2765-S3L



upper	cowhide suede leather NUBUCK in a thickness of 1,8 - 2,0 mm
lining	laminated breathable fabric MESH
inner insole	HI-POLY - anatomically shaped lightweight polyurethane foam coated with fabric MESH, antistatic
outsole	PU/PU - resistant to fuel oils, antistatic, antislip, double density injection
size	36 - 48
standard	EN ISO 20345:2011
version	S3 SRC - with plastic toe cap and kevlar midsole

Properties

PL Midsole penetration protection nonmetallic - PL	No
PS Midsole penetration protection nonmetallic - PS	No
SR Antislip prop. on ceramic with glycerol	No
WPA Water resistant upper	No
HRO Resist. of the outsole against contact heat	No
WR Water resistant	No
WRU Water resistant upper	Yes

ASTANA low cut safety shoes

» Shoes » Safety shoes » Low cut

CI Insulation against cold	No
HI Insulation of the outsole against heat	No
FO Resist. of the outsole against fuel oils	Yes
P Midsole penetration protection	Yes
E Energy absorption in the heel area	Yes
M Instep protection	No
A Antistatic properties	Yes
AN Ankle protection	No
CR Cut resistant upper	No
SRA Antislip prop. on ceramic tile with SLS	Yes
SRB Antislip prop. on smooth steel with glycerol	Yes
SRC Antislip resistance SRA + SRB	Yes
Free-tex Membrane	No
Michelin Michelin® sole	No
BOA BOA Fit System	No
NON-METALIC Footwear without metal parts	No
ESD antistatic properties ESD	No
Winter Winter footwear	No
ANTICUT Anti-cut boots	No
Standard	20345:2012
Shoe marking	S3

Logistics parameters

Velikost	Net weight	Gross weight	Sales box - widht	Sales box - length	Sales box - height	Group packaging - widht	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
36	0,98 kg	1,21 kg	200 mm	315 mm	120 mm	420 mm	600 mm	340 mm	13,20 kg	0,0 mm
37	1,02 kg	1,25 kg	200 mm	315 mm	120 mm	420 mm	600 mm	340 mm	13,20 kg	0,0 mm
38	1,11 kg	1,35 kg	200 mm	315 mm	120 mm	420 mm	600 mm	340 mm	14,20 kg	0,0 mm
39	1,14 kg	1,36 kg	200 mm	315 mm	120 mm	420 mm	600 mm	340 mm	14,40 kg	0,0 mm
40	1,14 kg	1,37 kg	200 mm	315 mm	120 mm	420 mm	600 mm	340 mm	14,20 kg	0,0 mm
41	1,17 kg	1,40 kg	200 mm	315 mm	120 mm	420 mm	600 mm	340 mm	14,60 kg	0,0 mm
42	1,18 kg	1,41 kg	200 mm	315 mm	120 mm	420 mm	600 mm	340 mm	14,80 kg	0,0 mm
43	1,24 kg	1,50 kg	205 mm	330 mm	120 mm	430 mm	620 mm	345 mm	15,80 kg	0,0 mm
44	1,25 kg	1,51 kg	205 mm	330 mm	120 mm	430 mm	620 mm	345 mm	16,00 kg	0,0 mm
45	1,33 kg	1,61 kg	205 mm	330 mm	120 mm	430 mm	620 mm	345 mm	16,40 kg	0,0 mm
46	1,31 kg	1,60 kg	210 mm	350 mm	130 mm	435 mm	650 mm	370 mm	17,00 kg	0,0 mm
47	1,39 kg	1,67 kg	210 mm	350 mm	130 mm	435 mm	650 mm	370 mm	17,80 kg	0,0 mm
48	1,43 kg	1,71 kg	210 mm	350 mm	130 mm	435 mm	650 mm	370 mm	17,80 kg	0,0 mm

Business parameters

Tarric	64034000
Country	CN
Weight	1,45 kg
Add Unit	NPR

ASTANA low cut safety shoes

» Shoes » Safety shoes » Low cut

Add Quantity 1