



VOLARE

S3L FO SR

KU474NA

CE EN ISO 20345:2022 S3L FO SR ESD

LOW SAFETY SHOE

36-47

KUBE Supergrip

Low safety shoe, MICRO-tech technical fabric thickness 1,8-2,0 mm.
Highly perspiring and abrasion resistant fabric lining
Shoe with refracting fabric insert.
Soft and lined tongue.

COMPLETELY METAL FREE SHOE
TOECAP 200J polymeric composite non-thermic according to EN 22568
PL MIDSOLE flexible antiperforation composite fabric according to EN 22568
SOLE KUBE bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping
INSOLE 5000 three-materials extracomfort: perspiring, removable, anatomic, absorbing, ESD and anti-bacterial

The shoes satisfies the requirement according to the norm IEC 61340-4-3:2017 (IEC 61340-5-1:2016) for the electrical resistance ESD

FO sole resistance to hydrocarbons
SR slip resistance

Size 36-47 Shoe weight Sz 42 gr. 475

AREAS OF APPLICATION

-  Logistics and Light Industry
-  Automotive Components
-  Metal and Wood Carpentry
-  ESD Area

CERTIFICATIONS APPLIED

-  **PL** Puncture Resistance with Non-Metallic Insert (nail Ø 4.5mm)
-  **SRC** Slip Resistant Sole
-  **WRU** Water-Repellent Upper

-  Slip Resistance (mandatory ceramic-Nals test)
-  **E** Heel Energy Absorption
-  **DGUV 112-191** DGUV 112-191

-  **A** Antistatic Footwear
-  **FO** Hydrocarbon Resistance

TECHNOLOGIES AND MATERIALS

-  **NO METAL** No metal
-  **ESD** ESD - Electrostatic Discharge
-  **NO METAL METAL FREE** Metal-Free
-  **HIGH VISIBILITY** High Visibility
-  **XL MONDO POINT 11** Mondo Point 11
-  **EXTRA LIGHT** Extreme Lightness
-  **SR** Slip Resistance (optional glycerin test)
-  **MICROTECH** Microtech

ANTI-SLIP RESULTS

*after simulation of walking by slight abrasion

Ceramic tile floor with NaLS	Forward heel (heel slip 7°) ≥ 0.31 ≥ 0.56	Backward heel (heel slip 7°) ≥ 0.36 ≥ 0.45	Ceramic tile floor with glycerin	Forward heel (heel slip 7°) ≥ 0.19 ≥ 0.35	Backward heel (heel slip 7°) ≥ 0.22 ≥ 0.35
SRA Ceramic + Nails	Flat ≥ 0.32 ≥ 0.39	Heel ≥ 0.28 ≥ 0.37	SRB Steel + Glicerol	Flat ≥ 0.18 ≥ 0.30	Heel ≥ 0.13 ≥ 0.20

↳ SOLE

KUBE Supergrip

Kube is a safety shoe with a young and sporty style, featuring a special highly slip resistant compound and specific inverted-profile cube-shaped lugs on the tread. Combined, these elements provide exceptional resistance on the slipperiest surfaces. This work shoe is therefore ideal for indoor environments. The sole is designed with reduced volume and height, ensuring both a lightweight feel and a look suitable for everyday wear. Thanks to its outstanding slip resistance, Kube has earned numerous field awards and passed rigorous tests—including the one for roof work (formerly UNI 11583:2015), one of the most challenging slip tests.

