

SOLDADOR S3

AC880BSP

CE UNI EN ISO 20345:2012 S3 SRC

High shoe, water-resistant WRU leather thickness 1,8-2,0 mm.
Perspiring and abrasion resistant fabric lining.
High visibility fabric insert. Lined and padded tongue.
Shoe with dross protective leather cover tongue and side closing by click buckle.

TOECAP 200J polymeric **composite non-thermic** according to EN 12568

MIDSOLE antiperforation steel according to EN 12568

SOLE ACTION bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

INSOLE 1000, in high density and open cells latex foam.

Absorbing, antistatic and perspiring

Size 39-47 Shoe weight Sz 42 gr. 635



CERTIFICATIONS



TECHNOLOGIES AND MATERIALS



SECTORS

 WOOD METAL CARPENTRY
WELDER

 BUILDING AND HEAVY INDUSTRY



SOLE



Action is a shoe studied for external jobs, with soft lines making it very light and comfortable.

PLUS

ANTISLIPPING TEST RESULTS

ANTISLIPPING TEST RESULTS			
SRC			
SHR	HEEL=0.528	0.38	
PLATE=0.528	0.38		
SHR	HEEL=0.528	0.38	
PLATE=0.528	0.38		