





ALASKA S3 CI WR

TO084B

CE UNI EN ISO 20345:2012 S3 CI WR SRC

Calf boot, WRU water resistant leather thickness 1,8-2,0 mm. Lining and tongue in felt with antibacterial aluminium. WinTherm® safety microfilm and ANTICOLD perspiring and abrasion resistant fur.

TOECAP 200J polymeric composite non-thermic according to EN

MIDSOLE flexible antiperforation composite fabric according to EN 12568

SOLE STABILE bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, antishock and anti-slipping SRC

INSOLE 5000, three-materials extracomfort: perspiring, removable, anatomic, absorbing, ESD and anti-bacterial CI insulated surface against cold -17°C

WR water resistant shoe Boot height sole included 24 cm

THIS PRODUCT COMPLIES WITH THE REQUIREMENTS OF THE STANDARD ASTM F2413-18:

- Impact resistant footwear (I)
- Compression resistant footwear (C)
- Puncture Resistant Footwear (PR)

Size 38-47 Shoe weight Sz 42 gr. 715



CERTIFICATIONS













TECHNOLOGIES AND MATERIALS









SECTORS



FARMING AND MINING



WOOD METAL CARPENTRY



BUILDING AND

HEAVY INDUSTRY





OIL AND GAS

SOLE



Stabile is the comfortable alternative to the classic and "heavy" shoe for building sector. This sole is highly performing with specific dowels, with dimensions and shapes to assure the maximum stability, with self-cleaning drainage channels to assure a perfect cleaning and with a soft compound to isolate the foot to the continuous shocks. Line studied with a lot of attention to the technology of uppers and lightness of the materials.

PLUS



 $\label{thm:wintherm:substitute} \begin{tabular}{ll} WINTHERM @ SAFETY guarantees the insulation from cold of the body through the substitute of the body through the body through the substitute of the body through the substitute of the body through the body$ the usage of two specific materials: this fibres of felt keeping the air inside the foot. This antibacterial material guarantees the highest breathability, permeability and water vapor coefficient foreseen by the regulation UNI EN ISO 20345.

ANTISLIPPING TEST RESULTS

